

PRODUCT DATASHEET

NAV-T 150 W SUPER 4Y

VIALOX® NAV®-T SUPER 4Y® 50...400 W | High-pressure sodium vapor lamps for open and enclosed luminaires



Areas of application

- Streets
- Outdoor lighting
- Industrial installations
- Suitable for use in open and enclosed luminaires
- Outdoor applications only in suitable luminaires

Product benefits

- Very high luminous efficacy
- Very good luminous flux maintenance throughout the life of the lamp
- Energy savings of up to 50 % when replacing mercury vapor lamps (HQL)
- Optimum energy efficiency on POWERTRONIC® PTo 3DIM ECGs



Product features

- Lamp survival factor: 95 % after 16,000 h burning time
- Lamp maintenance factor: ≥ 80 % after 16,000 h burning time (according to DIN 13201)
- Service lifetime: 4 years (at approx. 11 h/day)
- Dimmable on conventional control gears and electronic control gears



TECHNICAL DATA


Electrical data

Nominal wattage	150 W
Construction wattage	161.10 W
Nominal voltage	100 V
Ignition voltage	3.3/5.0 kVp ¹⁾
Nominal current	1.8 A
PFC capacitor at 50 Hz	20 µF

1) Minimum / Maximum


Photometrical data

Luminous flux	17500 lm
Luminous efficacy	109 lm/W
Color temperature	2000 K
Color rendering index Ra	≤25
Light color	220
Rated LLMF at 2,000 h	0.98
Rated LLMF at 4,000 h	0.97
Rated LLMF at 6,000 h	0.96
Rated LLMF at 8,000 h	0.95
Rated LLMF at 12,000 h	0.94
Rated LLMF at 16,000 h	0.94
Rated LLMF at 20,000 h	0.94
UV protection	No



Dimensions & Weight

Overall length	211.00 mm
----------------	-----------



Light center length (LCL)	132,0 mm
Diameter	47 mm
Product weight	115.00 g

Temperatures & operating conditions

Maximum permitted outer bulb temperature	310 °C
Maximum permitted base edge temperature	210 °C

Lifespan

Lifespan	32000 h
Rated lamp survival factor at 2,000 h	0.99
Rated lamp survival factor at 4,000	0.99
Rated lamp survival factor at 6,000	0.98
Rated lamp survival factor at 8,000 h	0.98
Rated lamp survival factor at 12,000 h	0.97
Rated lamp survival factor at 16,000	0.96
Rated lamp survival factor at 20,000 h	0.95
Lifespan B10	24000 h
Lifespan B5	20000 h
Lifespan B50	36000 h

Additional product data

Base (standard designation)	E40
Mercury content	21.6 mg
Design / version	Clear
Product remark	Important: Before replacing for NAV Standard lamps in existing installations, check that the igniters are suitable

Capabilities

Dimmable	Yes ¹⁾
Burning position	Any
Enclosed luminaire required	No

¹⁾ In combination with POWERTRONIC PTo

Certificates & Standards

Energy efficiency class	F
Energy consumption	162.00 kWh/1000h



Country-specific categorizations

ILCOS	ST-150-H/E/SL-E40-47/210
Order reference	NAV-T 150W SUPE

Energy labelling regulation data acc EU 2019/2015

Lighting technology used	HPS
Non-directional or directional	NDLS
Mains or non-mains	NMLS
Light source cap-type (or other electric interface)	E40
Connected light source (CLS)	No
Color-tuneable light source	No
Envelope	SECOND
High luminance light source	No
Anti-glare shield	No
Correlated colour temperature type	SINGLE_VALUE
Claim of equivalent power	No
Length	211.00 mm
Height	47 mm
Width	47 mm
Chromaticity coordinate x	0,535
Chromaticity coordinate y	0,420
Beam angle correspondence	SPHERE_360
EPREL ID	546583
Model number	AC34375

DOWNLOAD DATA

DOWNLOAD DATA	
	User instruction
	Certificates
	Certificates
	Declarations of conformity



LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4050300024400	Sleeve 1	52 mm x 52 mm x 260 mm	145.00 g	0.70 dm ³
4050300631790	Shipping box 12	245 mm x 266 mm x 200 mm	2043.00 g	13.03 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

