

# PRODUCT DATASHEET

## HALOSTAR STARLITE 50 W 12 V GY6.35

HALOSTAR STARLITE® 2000 | Low-voltage halogen lamps with pin base



### Areas of application

- General illumination
- Entrance lighting
- Accent lighting
- Lighting for reading
- Garden lighting
- Shops
- Restaurants, hotels and similar prestigious applications
- Offices, public buildings
- Outdoor applications only in suitable luminaires

### Product benefits

- Brilliant accent light
- Incredibly small dimensions for revolutionary new luminaire designs
- Approved for use in open luminaires (to IEC 60598-1)
- Axial filament for optimum directional light
- Special pins for corrosion protection
- UV filter
- Contains no mercury

### Product features

- Average life: 2,000 h
- 100 % dimmable
- Color rendering index Ra: 100




## TECHNICAL DATA

## Electrical data

Nominal wattage	50 W
Construction wattage	50.00 W
Nominal voltage	12 V

## Photometrical data

Luminous flux	910 lm
Luminous efficacy	18 lm/W
Light color (designation)	Warm White
Color temperature	2950 K
Color rendering index Ra	100
Light color	1029
UV protection	Yes



## Light technical data

Starting time	0.0 s
---------------	-------

## Dimensions &amp; Weight

Overall length	44.00 mm
Light center length (LCL)	30,0 mm
Diameter	12.00 mm
Product weight	2.2 g

## Lifespan

Lifespan	2000 h
Number of switching cycles	50000

**Additional product data**

Base (standard designation)	GY6.35
Mercury-free	Yes

**Capabilities**

Dimmable	Yes
Burning position	Any

**Certificates & Standards**

Energy efficiency class	G
Energy consumption	50.00 kWh/1000h

**Country-specific categorizations**

ILCOS	HSGST/C/UB-50-12-GY6.35-12/30
Order reference	64440 S AX 50W

**Energy labelling regulation data acc EU 2019/2015**

Lighting technology used	OTHER
Non-directional or directional	NDLS
Mains or non-mains	NMLS
Light source cap-type (or other electric interface)	GY6.35
Connected light source (CLS)	No
Color-tunable light source	No
Envelope	No
High luminance light source	No
Anti-glare shield	No
Correlated colour temperature type	SINGLE_VALUE
Claim of equivalent power	No
Length	44.00 mm
Height	12.00 mm
Width	12.00 mm
Chromaticity coordinate x	0.444
Chromaticity coordinate y	0.406
Beam angle correspondence	SPHERE_360
EPREL ID	714472
Model number	AC35301

## DOWNLOAD DATA

Photometric and lighting design files	
	Spectral power distribution

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075094277	Folding box 1	25 mm x 23 mm x 70 mm	4.20 g	0.04 dm <sup>3</sup>
4058075307728	Bundle 2	23 mm x 50 mm x 70 mm	9.00 g	0.08 dm <sup>3</sup>
4058075094284	Shipping box 40	144 mm x 107 mm x 121 mm	209.00 g	1.86 dm <sup>3</sup>
4058075307735	Shipping box 16	192 mm x 59 mm x 80 mm	111.00 g	0.91 dm <sup>3</sup>
4058075307742	Shipping box 192	366 mm x 201 mm x 176 mm	1495.00 g	12.95 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.