

## PRODUCT DATASHEET

### L 32 W/840 G10Q

LUMILUX® T9 C | Circular fluorescent lamps 29 mm, with G10Q base



#### Areas of application

- Public buildings
- Restaurants
- Industry
- Shops
- Supermarkets and department stores
- Hotels

#### Product benefits

- Excellent uniform illumination with no shadows

#### Product features

- Good color rendering index
- Single-ended round fluorescent lamp
- Dimmable




TECHNICAL DATA

Electrical data

|                      |         |
|----------------------|---------|
| Nominal wattage      | 32 W    |
| Construction wattage | 34.10 W |
| Nominal voltage      | 84 V    |
| Nominal current      | 0.45 A  |

Photometrical data

|                           |                    |
|---------------------------|--------------------|
| Luminous flux             | 2100 lm            |
| Luminous efficacy         | 62 lm/W            |
| Light color (designation) | LUMILUX Cool White |
| Color temperature         | 4000 K             |
| Color rendering index Ra  | ≥80                |
| Light color               | 840                |
| Rated LLMF at 2,000 h     | 0.80               |
| Rated LLMF at 4,000 h     | 0.74               |
| Rated LLMF at 6,000 h     | 0.72               |
| Rated LLMF at 8,000 h     | 0.70               |



Dimensions & Weight

|                |           |
|----------------|-----------|
| Overall length | 299.00 mm |
| Diameter       | 305 mm    |
| Tube diameter  | 29 mm     |
| Product weight | 176.00 g  |

Lifespan

|          |        |
|----------|--------|
| Lifespan | 9000 h |
|----------|--------|

|                                       |        |
|---------------------------------------|--------|
| Service life                          | 6300 h |
| Rated lamp survival factor at 2,000 h | 0.99   |
| Rated lamp survival factor at 4,000   | 0.95   |
| Rated lamp survival factor at 6,000   | 0.83   |
| Rated lamp survival factor at 8,000 h | 0.62   |
| Lifespan B50                          | 9000 h |

#### Additional product data

|                             |                 |
|-----------------------------|-----------------|
| Base (standard designation) | G10q            |
| Mercury content             | 4.8 mg          |
| Design / version            | LUMILUX version |

#### Capabilities

|          |     |
|----------|-----|
| Dimmable | Yes |
|----------|-----|

#### Certificates & Standards

|                         |                 |
|-------------------------|-----------------|
| Energy efficiency class | G               |
| Energy consumption      | 35.00 kWh/1000h |

#### Country-specific categorizations

|                 |                          |
|-----------------|--------------------------|
| ILCOS           | FSC-32/840-E-G10q-29/305 |
| Order reference | L 32W/840 C G10          |

#### Energy labelling regulation data acc EU 2019/2015

|                                                     |              |
|-----------------------------------------------------|--------------|
| Lighting technology used                            | OTHER_FL     |
| Non-directional or directional                      | NDLS         |
| Mains or non-mains                                  | NMLS         |
| Light source cap-type (or other electric interface) | G10q         |
| Connected light source (CLS)                        | No           |
| Color-tuneable light source                         | No           |
| Envelope                                            | No           |
| High luminance light source                         | No           |
| Anti-glare shield                                   | No           |
| Correlated colour temperature type                  | SINGLE_VALUE |
| Claim of equivalent power                           | No           |
| Length                                              | 299.00 mm    |
| Height                                              | 305 mm       |

|                           |            |
|---------------------------|------------|
| Width                     | 305 mm     |
| Chromaticity coordinate x | 0,380      |
| Chromaticity coordinate y | 0,380      |
| Beam angle correspondence | SPHERE_360 |
| EPREL ID                  | 546415     |
| Model number              | AC34190    |

## EQUIPMENT / ACCESSORIES

- Suitable for operation on electronic and conventional control gears

## Safety advice

- In case of lamp breakage: [www.ledvance.com/brokenlamp](http://www.ledvance.com/brokenlamp)

## DOWNLOAD DATA

| Documents and certificates                                                          |                               |
|-------------------------------------------------------------------------------------|-------------------------------|
|   | Declarations Of Conformity CE |
|   | Certificates                  |
| Photometric and lighting design files                                               |                               |
|  | Spectral power distribution   |

## LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume                |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4008321581143 | Sleeve<br>1                  | 310 mm x 301 mm x 37 mm              | 315.60 g     | 3.45 dm <sup>3</sup>  |
| 4008321581150 | Shipping box<br>12           | 460 mm x 322 mm x 318 mm             | 4228.20 g    | 47.10 dm <sup>3</sup> |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.