

PRODUCT DATASHEET

LS AY PFM -CSW-P2-50-COB

Connectors for COB LED Strips Performance Class | Connectors for COB LED Strips Performance Class



Areas of application

- General indoor illumination

Product benefits

- Easy installation of connector, no manual wiring required
- Tool-free installation

TECHNICAL DATA

Electrical data

| | |
|-----------------|-------|
| Nominal voltage | 24 V |
| Nominal current | 2.5 A |

Dimensions & Weight

| | |
|---------------------------------|---------------------|
| Length | 182.5 mm |
| Cable length | 150 mm |
| Width | 10 mm |
| Height | 4,0 mm |
| Cable cross-section, input side | 0.5 mm ² |
| Product weight | 3.15 g |

Temperatures & operating conditions

| | |
|--------------------------------|--------------|
| Ambient temperature range | -30...85 °C |
| Temperature range in operation | -30...+85 °C |

Certificates & Standards

| | |
|--------------------|------|
| Type of protection | IP00 |
|--------------------|------|

LOGISTICAL DATA

| | |
|------------------------------|--------------|
| Temperature range at storage | -40...+85 °C |
|------------------------------|--------------|

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4058075654099 | BAG 2 | 80 mm x 45 mm x 6 mm | 10.00 g | 0.02 dm ³ |
| 4058075654105 | Shipping box 300 | 353 mm x 147 mm x 200 mm | 1730.00 g | 10.38 dm ³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.