

# PRODUCT DATASHEET Indoor Garden Light Stand

Indoor Garden Light Stand 300 WT | Linear LED Grow Light with adjustable hight



#### Areas of application

- Indoor Gardening
- Kitchens
- Living areas

#### **Product benefits**

- Specially developed LED spectrum promotes photosynthesis in most plants
- Imitates day/night cycle by automatic timer operation

#### **Product features**

- Uses a combination of white full-spectrum LEDs and red LEDs
- Height of lamp head adjustable according to height of the plant



# **TECHNICAL DATA**

# Electrical data

Nominal wattage	14.00 W	
Nominal voltage	220240 V	
Mains frequency	5060 Hz	
Nominal current	110.000 mA	
Inrush current	14.1 A	
Max. no. of lum. on circuit break. B16 A	12	
Max. no. of lum. on circuit break. C10 A	12	
Max. no. of lum. on circuit break. C16 A	20	
Power factor $\lambda$	≥0.5	
Protection class	П	
Operating mode	Mains voltage	

# Photometrical data

Luminous flux	750 lm
Luminous efficacy	53 lm/W
Color temperature	3650 K
Light color (designation)	Neutral White
Color rendering index Ra	> 80
Standard deviation of color matching	< 6 sdcm
Photobiological safety group acc. to EN62778	RG0
Photobiological safety group acc. to EN62471	RG0
Beam angle	110°

# **Dimensions & Weight**

Length	440.00 mm
Width	180.00 mm
Height	310.00 mm
Product weight	555.00 g

### Materials & Colors

Product color	White
Housing color	White
Body material	Plastic METAL
Cover material	Polycarbonate (PC)
Mercury content	0.0 mg

# **Application & Mounting**

Ambient temperature range -20+40 °C		
Temperature range at storage	-20+70 °C	
Type of connection	Plug type C (EU)	
Type of protection	IP20	
Protection class IK (shock resistance)	IK03	
Dimmable	No	
Mounting type	Standing	
Mounting location	All surfaces	
Application environment	Indoor	
LED module replaceable	Not replaceable	

# Lifespan

Lifespan L70/B50 at 25 °C	25000 h	
Number of switching cycles	12500	

# **Emergency lighting**

Luminous flux in maintained operation mode	-
--	---

### Certificates & Standards

Standards
-----------

# **EQUIPMENT / ACCESSORIES**

- With two different brackets to adjust the height according to the plant underneath

### **DOWNLOAD DATA**

	DOWNLOAD DATA
PDF	User instruction

#### DOWNLOAD DATA



Declarations of conformity

#### **LOGISTICAL DATA**

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075576193	Folding box 1	57 mm x 502 mm x 72 mm	641.00 g	2.06 dm <sup>3</sup>
4058075576209	Shipping box 6	523 mm x 168 mm x 216 mm	4228.00 g	18.98 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.