

# PRODUCT DATASHEET

## ENDURA STYLE Mini Spot I 8 W DG

ENDURA® STYLE MINI SPOT | Wall luminaires with rotatable head



---

### Areas of application

- Outdoor use (IP44)
- Building facades
- Entrance lighting
- Patios, balconies

---

### Product benefits

- Easy and quick installation
- Energy-efficient thanks to LED technology

---

### Product features

- Bright and functional outdoor LED luminaires
- Die-cast aluminum housing
- Available in two housing colors
- Adjustable modules: rotation angle 340°



TECHNICAL DATA

Electrical data


|                        |               |
|------------------------|---------------|
| Nominal wattage        | 7.50 W        |
| Nominal voltage        | 220...240 V   |
| Mains frequency        | 50...60 Hz    |
| Power factor $\lambda$ | > 0.5         |
| Protection class       | I             |
| Operating mode         | Mains voltage |

Photometrical data

|                                                |                     |
|------------------------------------------------|---------------------|
| Luminous flux                                  | 320 lm              |
| Total luminous flux of contained light sources | 720 lm              |
| Luminous efficacy                              | 43 lm/W             |
| Color temperature                              | 3000 K              |
| Light color (designation)                      | Warm White          |
| Color rendering index Ra                       | > 80                |
| Standard deviation of color matching           | ≤6 sdc <sub>m</sub> |

Dimensions & Weight

|                |           |
|----------------|-----------|
| Length         | 100.00 mm |
| Width          | 110.00 mm |
| Height         | 54.00 mm  |
| Product weight | 390.00 g  |



Materials & Colors

|                |                               |
|----------------|-------------------------------|
| Product color  | Dark gray                     |
| Housing color  | Dark gray                     |
| Body material  | Aluminum                      |
| Cover material | Polymethylmethacrylate (PMMA) |

|                 |        |
|-----------------|--------|
| Mercury content | 0.0 mg |
|-----------------|--------|

Application & Mounting

|                              |                 |
|------------------------------|-----------------|
| Ambient temperature range    | -20...+40 °C    |
| Temperature range at storage | -20...+85 °C    |
| Type of connection           | Screw terminal  |
| Type of protection           | IP44            |
| Dimmable                     | No              |
| Mounting type                | Surface         |
| Mounting location            | Wall            |
| Application environment      | Outdoor         |
| LED module replaceable       | Not replaceable |

Lifespan

|                            |       |
|----------------------------|-------|
| Number of switching cycles | 15000 |
|----------------------------|-------|

Certificates & Standards

|           |                         |
|-----------|-------------------------|
| Standards | CE / EAC / REACH / RoHS |
|-----------|-------------------------|

EQUIPMENT / ACCESSORIES

- Complete mounting and connecting accessories included

DOWNLOAD DATA

| DOWNLOAD DATA                                                                      |                            |
|------------------------------------------------------------------------------------|----------------------------|
|  | User instruction           |
|  | Tender documents           |
|  | Declarations of conformity |
|  | Packaging insert           |

LOGISTICAL DATA



| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume               |
|---------------|------------------------------|--------------------------------------|--------------|----------------------|
| 4058075205130 | Folding box<br>1             | 70 mm x 142 mm x 123 mm              | 416.00 g     | 1.22 dm <sup>3</sup> |
| 4058075205147 | Shipping box<br>6            | 260 mm x 155 mm x 225 mm             | 2631.00 g    | 9.07 dm <sup>3</sup> |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

