

PRODUCT DATASHEET

LED SPOT GU10 4x2.6W 2700

LED SPOT GU10 | Ceiling mounted luminaires with adjustable GU10 spotlights



Areas of application

- Indoor applications
- Corridors, entrance areas, stairwells, living rooms, basements
- Kitchens, workspaces
- Ceiling and wall surface mounting

Product benefits

- Energy savings of up to 90 % compared to halogen lamp spotlights
- Timeless design
- Flexible thanks to replaceable LED lamps
- Easy mounting

Product features

- Luminaire family features five versions with up to 6 spot heads
- Housing surface made of brushed nickel
- Adjustable head



TECHNICAL DATA

Electrical data


Nominal wattage	10.40 W
Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Nominal current	100.000 mA
Inrush current	12 A
Max. no. of lum. on circuit break. B16 A	13
Max. no. of lum. on circuit break. C10 A	13
Max. no. of lum. on circuit break. C16 A	21
Power factor λ	> 0.4
Protection class	I
Operating mode	Mains voltage

Photometrical data

Luminous flux	920 lm
Total luminous flux of contained light sources	920 lm
Luminous efficacy	88 lm/W
Color temperature	2700 K
Light color (designation)	Warm White
Color rendering index Ra	> 80
Standard deviation of color matching	≤ 6 sdc _{cm}
Photobiological safety group acc. to EN62778	RG1
Photobiological safety group acc. to EN62471	RG1
Beam angle	36 °

Dimensions & Weight

Length	486.00 mm
Width	90.00 mm
Height	170.00 mm
Product weight	810.00 g



Materials & Colors

Product color	Silver
Housing color	Silver
Body material	Aluminum
Cover material	Glass
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-20...+40 °C
Temperature range at storage	-20...+80 °C
Type of connection	Screw terminal
Type of protection	IP20
Protection class IK (shock resistance)	IK03
Dimmable	No
Mounting type	Surface
Mounting location	Ceiling / Wall
Application environment	Indoor
Adjustable	Yes
With light source	Yes
Holder designation	G10

Lifespan

Lifespan L70/B50 at 25 °C	15000 h
Number of switching cycles	15000

Certificates & Standards

Standards	CE / EAC / REACH / RoHS
-----------	-------------------------

Additional product data

Product remark	Maximum bulb wattage: 50 W
----------------	----------------------------

EQUIPMENT / ACCESSORIES

- Equipped with OSRAM LED LAMP EAN 4058075233263
- Complete mounting and connecting accessories included



DOWNLOAD DATA

DOWNLOAD DATA	
	User instruction
	Declarations of conformity
	Declarations of conformity

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075540583	Folding box 1	150 mm x 210 mm x 390 mm	954.00 g	12.29 dm ³
4058075540590	Shipping box 4	400 mm x 260 mm x 330 mm	4379.00 g	34.32 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.