

PRODUCT DATASHEET

LED WORKLIGHT BATTERY 30W

WORKLIGHTS BATTERY | Mobile battery powered worklight



Areas of application

- Renovation
- Garages
- Basement
- Workshops

Product benefits

- Energy savings of up to 80% compared to halogen lamp worklights
- Independent of power supply due to battery technology

Product features

- Worklight with swiveling head
- Battery discharge time: up to 4 h
- Battery rechargeable via USB cable



TECHNICAL DATA

Electrical data

Nominal wattage	30 W
Nominal voltage	5 V
Mains frequency	50...60 Hz
Nominal current	130.000 mA
Inrush current	60 A
Max. no. of lum. on circuit break. B16 A	3
Max. no. of lum. on circuit break. C10 A	3
Max. no. of lum. on circuit break. C16 A	6
Power factor λ	> 0.4
Protection class	I
Operating mode	Battery

Photometrical data

Luminous flux	2400 lm
Total luminous flux of contained light sources	2500 lm
Luminous efficacy	80 lm/W
Color temperature	4000 K
Light color (designation)	Cool White
Color rendering index Ra	≥80
Standard deviation of color matching	< 6 sdcn
Flickering metric (Pst LM)	≤1 %
Stroboscope effect metric (SVM)	≤0.4
Photobiological safety group acc. to EN62778	RG1
Photobiological safety group acc. to EN62471	RG1
Beam angle	110 °

Dimensions & Weight

Length	311.00 mm
Width	200.00 mm
Height	316.00 mm
Product weight	2300.00 g

Materials & Colors

Product color	Orange
Housing color	Orange
Body material	Aluminum Plastic
Cover material	Polycarbonate (PC)
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-10...+40 °C
Temperature range at storage	-20...+50 °C
Type of protection	IP44
Protection class IK (shock resistance)	IK05
Dimmable	No
Mounting type	Standing
Mounting location	Floor
LED module replaceable	Not replaceable

Lifespan

Lifespan L70/B50 at 25 °C	25000 h
Number of switching cycles	15000

Emergency lighting

Luminous flux in maintained operation mode	-
Luminous flux in emergency operation mode	2400 lm
Nominal voltage of battery	5 V
Battery life in emergency operation mode	4 h
Battery charging time	8 h

Certificates & Standards

Standards	RoHS / REACH / CE
Luminaire with limited surface temperature, "D sign"	No

EQUIPMENT / ACCESSORIES

- USB charging cable

DOWNLOAD DATA

DOWNLOAD DATA	
	User instruction
	Declarations of conformity

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075576513	Folding box 1	325 mm x 209 mm x 317 mm	2580.00 g	21.53 dm ³
4058075576520	Shipping box 4	680 mm x 448 mm x 358 mm	11465.00 g	109.06 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

