

# PRODUCT DATASHEET ENDURA STYLE PLATE Wall Sensor 12,5W

ENDURA STYLE PLATE | Stainless steel wall luminaires with indirect illumination



#### Areas of application

- Building facades
- Entrance lighting
- Patios, balconies

#### **Product benefits**

- Easy and quick installation
- Energy-efficient thanks to LED technology

#### **Product features**

- Bright and functional outdoor LED luminaires
- Available with and without motion sensor
- Stainless steel housing
- Type of protection: IP44



## **TECHNICAL DATA**

## Electrical data


Nominal wattage	12.50 W
Nominal voltage	220240 V
Mains frequency	5060 Hz
Power factor $\lambda$	≥0.5
Protection class	П
Operating mode	Mains voltage

## Photometrical data

Luminous flux	630 lm
Total luminous flux of contained light sources	1500 lm
Luminous efficacy	48 lm/W
Color temperature	3000 K
Light color (designation)	Warm White
Color rendering index Ra	≥80
Standard deviation of color matching	< 6 sdcm
Beam angle	108 °

# **Dimensions & Weight**

Length	60.00 mm
Width	180.00 mm
Height	283.00 mm
Product weight	680.00 g



## Materials & Colors

Product color	Steel
Housing color	Steel
Body material	Steel
Cover material	Polycarbonate (PC)

# **Application & Mounting**

Ambient temperature range	-20+40 °C	
Type of connection	Terminal, 2-Pole (L, N)	
Type of protection	IP44	
Dimmable	No	
Mounting type	Surface	
Mounting location	Wall	
Application environment	Outdoor	
LED module replaceable	Not replaceable	

## Lifespan

Lifespan L70/B50 at 25 °C	25000 h
Number of switching cycles	12500

## Sensor

Type of sensor	Light / Motion	
Sensor technology	Passive infrared (PIR)	
Sensor detection angle	100 °	
Sensor controlled switching time	10 s4 min	
Detection range of motion sensor	58 m	
Detection threshold of daylight sensor	102000 lx	

## Certificates & Standards

Standards	CE / EAC / REACH / RoHS
-----------	-------------------------

# **EQUIPMENT / ACCESSORIES**

- Complete mounting and connecting accessories included

## **DOWNLOAD DATA**

	DOWNLOAD DATA
POF	User instruction
	Tender documents
PDF	Declarations of conformity

## **LOGISTICAL DATA**

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075477872	Folding box 1	65 mm x 185 mm x 290 mm	756.00 g	3.49 dm <sup>3</sup>
4058075477889	Shipping box 4	310 mm x 280 mm x 205 mm	3.39 g	17.79 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.