

PRODUCTINFORMATIEBLAD

Touch DIM LS/PD LI

Touch DIM® LS/PD LI | Licht- en aanwezigheidssensoren voor lichtmanagementsystemen



Toepassingsgebieden

- Single luminaires in office areas

Productvoordelen

- A setpoint for daylight-dependent control can be stored by double clicking
- Operated via standard switches

Productkenmerken

- Touch DIM light and presence sensor
- Can also be operated purely as a presence sensor
- Maximum signal line length: 10 m
- Maximum power input: 0.5 W
- Delay time: 15 min

TECHNISCHE GEGEVENS

ELEKTRISCHE GEGEVENS

Nominale vermogen	0,50 W
Nominale spanning	220...240 V
Netfrequentie	50 Hz

AFMETINGEN & GEWICHT

Lengte	63.00 mm
Breedte	29.00 mm
Breedte (incl. ronde armaturen)	29.00 mm
Hoogte	21.00 mm
Hoogte (incl. cylin. armaturen)	21.00 mm
Product gewicht	24,00 g

KLEUREN & MATERIALEN

Kleur van het product	Antraciet
-----------------------	-----------

TEMPERATUREN & BEDRIJFSOMSTANDIGHEDEN

Omgevingstemperatuur bereik	0...+50 °C
-----------------------------	------------

MOGELIJKHEDEN

Dimmable	Nee
Dimmer interface	Touch DIM
Maximale kabellengte E-VSA/lamp REM	10 m
Aantal stuuruitgangen	1
Maximale inbouwhoogte	4 m
Detectie hoek	80 ° 1)
Type montage	Inbouwarmatuur
Bereik van de lichtsensor	10...350 lx 2)

1) Ongeveer

2) Bij benadering, gemeten bij de sensor

CERTIFICATEN & NORMEN

Keurmerken	CE
Veiligheidsklasse	II
Type bescherming	IP20

EQUIPMENT / ACCESSORIES

– Suitable for up to 4 QTi DALI ECG or 4 HTi DALI transformers or 4 OTi DALI LED drivers

DOWNLOADS

DOWNLOADS	
	User instruction
	User instruction
	User instruction
	User instruction
	Certificates
	Declarations of conformity
	CAD data
	CAD data
	CAD data PDF
	CAD data PDF
	Advertisements
	Advertisements

LOGISTIEKE GEGEVENS

Productcode	Verpakkingseenheid (stuks per verpakking)	Afmetingen (lengte x breedte x hoogte)	Brutogewicht	Volume
4008321023025	Vouwdooos 1	215 mm x 35 mm x 43 mm	57.57 g	0.32 dm ³
4008321023032	Verzenddooos 25	217 mm x 180 mm x 217 mm	1617.14 g	8.48 dm ³

De genoemde productcodes beschrijven de kleinste hoeveelheid die besteld kan worden. Eén verzendeenheid kan bestaan uit één of meer afzonderlijke producten. Bij het plaatsen van een order enkele of veelvouden van de verpakkingseenheid invoeren.

DISCLAIMER

Onder voorbehoud van verandering zonder kennisgeving. Fouten en drukfouten voorbehouden. Zorg ervoor dat u de meest recente versie gebruikt.

