

PRODUCTINFORMATIEBLAD DALIECO CONTROL

DALieco Control | Besturingseenheden voor lichtmanagementsystemen



Toepassingsgebieden

- Offices
- Classrooms
- Training rooms
- Corridors
- Ceiling or independent installation via ECO CI KIT possible

Productvoordelen

- VDE/VDE EMC certified system
- Simplified startup thanks to predefined operation modes
- Automatic and manual setting of regulation set point

Productkenmerken

- 2 channel light control with DALI interface
- Daylight-dependent regulation and presence-dependent control of light
- 100 hours burn-in function for fluorescent lamps
- Operation via standard pushbutton or IR remote control
- Outputs with adjustable offset
- Outputs with electronical reversible overtemperature, short-circuit, overload protection
- Connection of up to 4 DALieco LS/PD LI or 6 DALI LS/PD LI sensors
- Connection of up to 4 light and presence sensors via 4p4c plug system
- Individual adjustment of functional parameters via IR remote control
- Halogen free polycarbonate plastic housing
- Sensor connection via polarity reversal protected 4p4c socket (RJ10)

TECHNISCHE GEGEVENS

ELEKTRISCHE GEGEVENS

Nominale vermogen	4,00 W
Nominale spanning	230 V
Netfrequentie	50/60 Hz

AFMETINGEN & GEWICHT

Lengte	118.00 mm
Montage gat afstand, lengte	110,0 mm
Breedte	30.00 mm
Breedte (incl. ronde armaturen)	30.00 mm
Hoogte	21.00 mm
Hoogte (incl. cylin. armaturen)	21.00 mm
Product gewicht	48,5 g

TEMPERATUREN & BEDRIJFSOMSTANDIGHEDEN

Omgevingstemperatuur bereik	-20...+50 °C
-----------------------------	--------------

MOGELIJKHEDEN

Dimmable	Nee
Dimmer interface	DALI
Aantal stuuruitgangen	2
Type montage	Inbouwarmatuur

CERTIFICATEN & NORMEN

Keurmerken	CE
Veiligheidsklasse	II
Type bescherming	IP20

EQUIPMENT / ACCESSORIES

- Suitable for up to 32 electronic control gears

DOWNLOADS

DOWNLOADS	
	User instruction
	User instruction

DOWNLOADS

	User instruction
	User instruction
	PRODUCTINFORMATIEBLAD
	Declarations of conformity
	Declarations of conformity
	CAD data 3-dim
	CAD data 3-dim
	Advertisements

LOGISTIEKE GEGEVENS

Productcode	Verpakkingseenheid (stuks per verpakking)	Afmetingen (lengte x breedte x hoogte)	Brutogewicht	Volume
4008321988645	Vouwdoos 1	45 mm x 45 mm x 170 mm	111.50 g	0.34 dm ³
4008321789297	Verzenddoos 25	240 mm x 238 mm x 189 mm	3194.00 g	10.80 dm ³

De genoemde productcodes beschrijven de kleinste hoeveelheid die besteld kan worden. Eén verzendeenheid kan bestaan uit één of meer afzonderlijke producten. Bij het plaatsen van een order enkele of veelvouden van de verpakkingseenheid invoeren.

DISCLAIMER

Onder voorbehoud van verandering zonder kennisgeving. Fouten en drukfouten voorbehouden. Zorg ervoor dat u de meest recente versie gebruikt.