

PRODUCT DATASHEET

SP RING D133 WT

SPOT RING | Refurbishment rings to reduce existing cut-out in recessed ceilings

Areas of application

- Refurbishment of existing cut-outs in recessed ceilings



Product benefits

- Retrofit: Replacement of old recessed lights with LEDVANCE SPOTs FIX or ADJ in latest LED-technology
- Standardize: Reduce existing cut-outs to a standard cut-out of 68 mm
- Versatile: Refurbishment rings for padding cut-out holes from Ø68 - Ø115 or Ø115 - Ø160 mm

Product features


- Material: deep-drawn steel
- Suitable only for LEDVANCE SPOTs in 68 mm cut-out
- Silicon-pad protected springs



TECHNICAL DATA

Dimensions & Weight

Diameter	133 mm
Height	3 mm
Product weight	62.00 g



Materials & Colors

Product color	White
Body material	Steel

Application & Mounting

Ambient temperature range	-20...+40 °C
Mounting type	Recessed
Mounting location	Ceiling
Mounting diameter	68...115 mm

Certificates & Standards

Standards	CE / CB / UKCA / EAC
-----------	----------------------

Additional product data

Product remark	Available from November 2022
----------------	------------------------------

DOWNLOAD DATA

DOWNLOAD DATA	
	User instruction
	User instruction
	User instruction

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854013355	BAG 1	135 mm x 135 mm x 3 mm	66.00 g	0.05 dm ³
4099854013362	Shipping box 20	145 mm x 145 mm x 70 mm	1380.00 g	1.47 dm ³
4099854013379	Shipping box 160	310 mm x 305 mm x 170 mm	11296.00 g	16.07 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.