

# PRODUCT DATASHEET LS AY PFM -CP-P2-500 COB

Connectors for COB LED Strips Performance Class | Connectors for COB LED Strips Performance Class

### Areas of application

- General indoor illumination



## **Product benefits**

- Easy installation of connector, no manual wiring required
- Tool-free installation

# **TECHNICAL DATA**

# **Electrical data**

Nominal voltage	24 V
Nominal current	2.5 A

# **Dimensions & Weight**

Length	516.25 mm
Cable length	500 mm
Width	10 mm
Height	4,0 mm
Cable cross-section, input side	0.5 mm <sup>2</sup>
Product weight	7.15 g

# Temperatures & operating conditions

Ambient temperature range	-3085 °C
Temperature range in operation	-30+85 °C

## Certificates & Standards

Type of protection	IP00
71 1	

# **LOGISTICAL DATA**

Temperature range at storage	-40+85 °C
------------------------------	-----------

# **LOGISTICAL DATA**

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075654075	BAG 2	90 mm x 70 mm x 7 mm	19.30 g	0.04 dm <sup>3</sup>
4058075654082	Shipping box 150	353 mm x 147 mm x 200 mm	1633.00 g	10.38 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.