

# PRODUCT DATASHEET SMART+WIFI CEILING FAN Round + Remote control

Smart wifi ceiling fan | Smart Wifi Ceiling fans for various appliaction areas, combining light and air ventilation



#### Areas of application

- Kitchens, living rooms, children's rooms or home offices
- For indoor use only

#### **Product benefits**

- Clean design, allows for an easy combination with various room styles
- Easy mounting

#### **Product features**

- Network protocol: WiFi
- Luminaire with integrated air ventilation
- Adjustable air speed
- Smart control for adjustable color temperature and RGB color control
- Controllable via LEDVANCE SMART+ WiFi App (with minimum Android™ 4.4 or iOS 10.0)
- Remote control included for network independant operation



# **TECHNICAL DATA**

# Electrical data

Nominal wattage	74.00 W
Nominal voltage	3,6 V
Mains frequency	5060 Hz
Nominal current	10.000 mA
Power factor $\lambda$	> 0.90
Protection class	П
Operating mode	Mains voltage

#### Photometrical data

Luminous flux	3050 lm	
Total luminous flux of contained light sources	4100 lm	
Luminous efficacy	131 lm/W	
Color temperature	30006500 K	
Light color (designation)	Tunable White	
Color rendering index Ra	> 80	
Standard deviation of color matching	< 6 sdcm	
Photobiological safety group acc. to EN62778	RGO	
Photobiological safety group acc. to EN62471	RG0	
Beam angle	110 °	

# Dimensions & Weight

Length	602.00 mm
Width	600.00 mm
Height	216.00 mm
Product weight	3000.00 g

## Materials & Colors

Product color	White
Housing color	White



Body material Acrylonitrile butadiene styrene (ABS)	
Cover material	Polycarbonate (PC)
Mercury content	0.0 mg

# **Application & Mounting**

Ambient temperature range	-20+40 °C	
Temperature range at storage	-20+80 °C	
Type of connection	Terminal	
Type of protection	IP20	
Dimmable	Yes	
Type of dimming	WiFi	
Mounting type	Surface	
Mounting location	Ceiling	
Application environment	Indoor	
LED module replaceable	Not replaceable	

#### Lifespan

Lifespan L70/B50 at 25 °C	30000 h	
Number of switching cycles	15000	

# **Emergency lighting**

Type of emergency operation test	None

## Certificates & Standards

Standards CE / ERP / UKCA
---------------------------

# **EQUIPMENT / ACCESSORIES**

- Complete mounting and connecting accessories included
- Control via app or voice control requires compatible Smart home system
- For control via LEDVANCE SMART + WiFi App, a smart phone or Tablet PC is required
- Remote control included

# **DOWNLOAD DATA**

# DOWNLOAD DATA User instruction

	DOWNLOAD DATA
PDF	Declarations of conformity
PDF	Declarations of conformity

#### **LOGISTICAL DATA**

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075572553	Folding box 1	216 mm x 600 mm x 602 mm	3688.00 g	78.02 dm³
4058075572560	Shipping box 2	620 mm x 452 mm x 620 mm	9235.00 g	173.75 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

