

PRODUCT DATASHEET LS AY -PW03/U/26X26/14/1

LED STRIP PERFORMANCE-300 PROTECTED | High performance IP66 protected LED strips with 300 lm/m for high requirements



Areas of application

- General indoor illumination

Product benefits

- Robust aluminum profile
- Quick and simple installation

TECHNICAL DATA

Dimensions & Weight

Length	1000 mm
Width	26,0 mm
Height	26,0 mm
Product weight	240.00 g

Colors & materials

Product color	Grey
	· •

Temperatures & operating conditions

Ambient temperature range	-15+45 °C	
Temperature range in operation	-15+45 °C	

Additional product data

Product remark Can be combined with all LEDVANCE LED Strips including connect and endcap	ors
---	-----

LOGISTICAL DATA

Temperature range at storage	-35+85 °C
------------------------------	-----------

DOWNLOAD DATA

DOWNLOAD DATA



Catalogs

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075278165	BAG 1	1,200 mm x 50 mm x 5 mm	241.00 g	0.30 dm ³
4058075278172	Bundle 10	500 mm x 55 mm x 50 mm	2412.00 g	1.38 dm ³
4058075278189	Shipping box 50	1,030 mm x 160 mm x 310 mm	12871.00 g	51.09 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.