

PRODUCT DATASHEET

LS VAL -600/830/30/IP65

LED STRIP VALUE-600 30 meter reel | IP65 protected LED strips 30m long with 600 lm/m for general applications



Areas of application

- General outdoor illumination
- Cove lighting
- Bars, restaurants, hotels
- Residential interiors

Product benefits

- Long LED strips for customized solutions made to measure
- Great design freedom thanks to flexibility and cuttability of module
- Suitable for use in damp conditions thanks to high type of protection
- Easy mounting on many smooth surfaces thanks to self-adhesive tape at the back
- Maximum flexibility due to large range of accessories
- Easy installation, no tools required for connection

Product features

- Flexible and cuttable LED strip
- Luminous flux: 600 lm/m
- Color rendering index R_a : > 80
- Lifetime (L70/B50): up to 20,000 h at T_c max.: 75°C
- Smallest cuttable unit: 100 mm
- Available with color temperature: 3,000 K, 4,000 K, 6,500 K
- Type of protection: IP65



- Dimmable with suitable drivers, see also www.ledvance.com/dim

TECHNICAL DATA

Electrical data

Nominal wattage	27.50 W
Construction wattage	27.50 W
Nominal wattage per meter	6.1 W ¹⁾
Nominal voltage	24 V
Reverse Voltage	30 V
Type of current	DC

¹⁾ Value based on first meter of the product

Photometrical data

Luminous efficacy	90 lm/W ¹⁾
Luminous flux	2500 lm
Luminous flux per meter	560 lm ¹⁾
Color temperature	3000 K
Color rendering index Ra	> 80
Light color LED	White
Light color (designation)	White
Standard deviation of color matching	≤5 sdcm

¹⁾ Value based on first meter of the product


Light technical data

Beam angle	110 °
------------	-------

LED MODULE INFORMATION

Number of LEDs per meter	60
Number of LEDs per smallest unit	6

Dimensions & Weight



Length	30000.00 mm
Length – smallest unit	100 mm
Cable length	500.000
Width	10.00 mm
Height	4.00 mm
Prewired	Yes
LED pitch	16.67 mm
Short pitch	No
Product weight	2200.00 g

Colors & materials

Cover material	Silicone
----------------	----------

Temperatures & operating conditions

Ambient temperature range	-20...+40 °C
Maximum temperature at tc test point	75 °C
Temperature range in operation	-20...+40 °C

Lifespan

Nominal lamp life time	20000 h
------------------------	---------

Capabilities

Dimmable	Yes ¹⁾
Lowest bending radius	15,0 mm
Self-adhesive	Yes

¹⁾ Dimmable with suitable drivers, see also www.ledvance.com/dim

Certificates & Standards

Approval marks – approval	CE
Protection class	III
Type of protection	IP65
Energy consumption	3.10 kWh/1000h ¹⁾
Energy class of contained Light source	G
Salt mist resistance acc. IEC 60068-2-52	No
UV resistance acc. IEC 60068-2-5	Yes

¹⁾ Value based on 0.5 meter



LOGISTICAL DATA

Temperature range at storage	-20...+80 °C
------------------------------	--------------

Energy labelling regulation data acc EU 2019/2015

EPREL ID	618776
Model number	AC32634

EQUIPMENT / ACCESSORIES

- Connectors, profiles and covers for several mounting options available

DOWNLOAD DATA

DOWNLOAD DATA	
	Addon Technical Information
	Declarations of conformity

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075597464	Folding box 1	242 mm x 242 mm x 26 mm	2626.00 g	1.52 dm ³
4058075600850	Shipping box 3	516 mm x 496 mm x 332 mm	8872.00 g	84.97 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.