


# PRODUCT DATASHEET

## Vintage 1906 NEST DIM 33 4.8 W/2200 K E27

Vintage 1906 LED DIM | LED lamps, dimmable vintage edition



### Areas of application

- Perfect for decorative installations
- Domestic applications
- General illumination
- Outdoor use in suitable outdoor luminaires only

### Product benefits

- Very low energy consumption
- Instant 100 % light, no warm-up time
- Can be easily fitted instead of ordinary light bulbs
- Lamps with innovative LED "filament" technology

### Product features

- LED lamps for line voltage
- Lamp made of glass
- Lifetime: up to 15,000 h
- Beam angle: up to 360°
- Dimmable
- Good quality of light; color rendering index  $R_a \geq 80$ ; constant chromaticity




## TECHNICAL DATA

### Electrical data

|                                          |             |
|------------------------------------------|-------------|
| Nominal wattage                          | 4.8 W       |
| Construction wattage                     | 4.80 W      |
| Nominal voltage                          | 220...240 V |
| Claimed equiv. conventional lamp power   | 33 W        |
| Nominal current                          | 26 mA       |
| Type of current                          | AC          |
| Inrush current                           | 0.08 A      |
| Operating frequency                      | 50/60 Hz    |
| Mains frequency                          | 50/60 Hz    |
| Max. lamp no. on circuit break. 10 A (B) | 307         |
| Max. lamp no. on circuit break. 16 A (B) | 492         |
| Power factor $\lambda$                   | > 0.50      |

### Photometrical data

|                                         |                    |
|-----------------------------------------|--------------------|
| Luminous flux                           | 360 lm             |
| Nominal useful luminous flux 90°        | 360 lm             |
| Luminous efficacy                       | 75 lm/W            |
| Lumen main.fact.at end of nom.life time | 0.93               |
| Light color (designation)               | Comfort warm white |
| Color temperature                       | 2200 K             |
| Color rendering index Ra                | ≥80                |
| Light color                             | 822                |
| Standard deviation of color matching    | ≤6 sdcm            |
| Rated LLMF at 6,000 h                   | 0.80               |
| Flickering metric (Pst LM)              | ≤1                 |
| Stroboscope effect metric (SVM)         | ≤0,4               |



Light technical data

|                                    |          |
|------------------------------------|----------|
| Beam angle                         | 320 °    |
| Warm-up time (60 %)                | < 0.50 s |
| Starting time                      | < 0.5 s  |
| Rated beam angle (half peak value) | 320.00 ° |

Dimensions & Weight



|                  |           |
|------------------|-----------|
| Overall length   | 405.00 mm |
| Diameter         | 200.00 mm |
| Maximum diameter | 200 mm    |
| Product weight   | 430.00 g  |

Temperatures & operating conditions

|                                      |              |
|--------------------------------------|--------------|
| Ambient temperature range            | -20...+40 °C |
| Maximum temperature at tc test point | 46,2 °C      |

Lifespan

|                                     |         |
|-------------------------------------|---------|
| Lifespan                            | 15000 h |
| Number of switching cycles          | 100000  |
| Lumen maintenance at end of serv    | 0.93    |
| Rated lamp survival factor at 6,000 | ≥ 0.90  |

Additional product data

|                             |        |
|-----------------------------|--------|
| Base (standard designation) | E27    |
| Mercury content             | 0.0 mg |
| Design / version            | Clear  |

Capabilities

|          |     |
|----------|-----|
| Dimmable | Yes |
|----------|-----|

Certificates & Standards

|                         |   |
|-------------------------|---|
| Energy efficiency class | G |
|-------------------------|---|

|                                              |                         |
|----------------------------------------------|-------------------------|
| Energy consumption                           | 5.00 kWh/1000h          |
| Type of protection                           | IP20                    |
| Standards                                    | CE / ROHS / REACH / ERP |
| Photobiological safety group acc. to EN62778 | RG0                     |

### Country-specific categorizations

|                 |                 |
|-----------------|-----------------|
| Order reference | 1906LNESTD 4,8W |
|-----------------|-----------------|

### LOGISTICAL DATA

|                              |              |
|------------------------------|--------------|
| Temperature range at storage | -20...+80 °C |
|------------------------------|--------------|

### Energy labelling regulation data acc EU 2019/2015

|                                                      |                |
|------------------------------------------------------|----------------|
| Lighting technology used                             | LED            |
| Non-directional or directional                       | NDLS           |
| Mains or non-mains                                   | MLS            |
| Light source cap-type (or other electric interface)  | E27            |
| Connected light source (CLS)                         | No             |
| Color-tuneable light source                          | No             |
| Envelope                                             | No             |
| High luminance light source                          | No             |
| Anti-glare shield                                    | No             |
| Correlated colour temperature type                   | SINGLE_VALUE   |
| Standby power                                        | 0 W            |
| Networked standby power for CLS                      | not applicable |
| Claim of equivalent power                            | Yes            |
| Length                                               | 405.00 mm      |
| Height                                               | 200.00 mm      |
| Width                                                | 200.00 mm      |
| Chromaticity coordinate x                            | 0,502          |
| Chromaticity coordinate y                            | 0,415          |
| Beam angle correspondence                            | SPHERE_360     |
| Survival factor                                      | 0,90           |
| Displacement factor                                  | ≥0,50          |
| LED light source replaces a fluorescent light source | No             |
| EPREL ID                                             | 1213089        |
| Model number                                         | AC41938        |

## LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume                 |
|---------------|------------------------------|--------------------------------------|--------------|------------------------|
| 4058075761834 | Folding box<br>1             | 227 mm x 227 mm x 468 mm             | 743.00 g     | 24.12 dm <sup>3</sup>  |
| 4058075761841 | Shipping box<br>4            | 470 mm x 470 mm x 496 mm             | 4313.00 g    | 109.57 dm <sup>3</sup> |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.