

PRODUCT DATASHEET

DoorLED Down Silver

Door LED Down | Mobile luminaire for entrance areas, light outlet down



Areas of application

- For a very large range of uses
- Indoor and outdoor
- Entrance lighting
- Corridors
- Patios, balconies

Product benefits

- Attractive and functional design
- Economical operation due to low power consumption
- Easy and quick installation
- Accessories for flexible mounting options included

Product features

- Integrated light and motion sensor
- Available in two housing colors
- Type of protection: IP54



TECHNICAL DATA

Electrical data


Nominal wattage	0.95 W
Nominal voltage	4,5 V
Mains frequency	0 Hz
Nominal current	210.000 mA
Max. no. of lum. on circuit break. B16 A	-
Max. no. of lum. on circuit break. C10 A	-
Max. no. of lum. on circuit break. C16 A	-
Protection class	III
Operating mode	Battery

Photometrical data

Luminous flux	40 lm
Luminous efficacy	42 lm/W
Color temperature	4000 K
Light color (designation)	Cool White
Color rendering index Ra	> 80
Standard deviation of color matching	≤6 sdcn

Dimensions & Weight

Length	102.50 mm
Width	92.40 mm
Height	36.50 mm
Product weight	154.00 g



Materials & Colors

Product color	Silver
---------------	--------

Housing color	Silver
Body material	Polycarbonate (PC)
Cover material	Acrylonitrile butadiene styrene (ABS)
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-10...+40 °C
Temperature range at storage	-20...+50 °C
Type of protection	IP54
Dimmable	No
Mounting type	Surface
Mounting location	Wall
Application environment	Outdoor
LED module replaceable	Not replaceable

Lifespan

Lifespan L70/B50 at 25 °C	25000 h
Number of switching cycles	10000

Sensor

Type of sensor	Light / Motion
Sensor technology	Passive infrared (PIR)
Detection range of motion sensor	5000 mm

Certificates & Standards

Standards	CE / EAC / REACH / RoHS
-----------	-------------------------

EQUIPMENT / ACCESSORIES

– Batteries included: 4x 1.5 V LR6 (AA)

DOWNLOAD DATA

DOWNLOAD DATA	
	Tender documents
	Declarations of conformity

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075267824	Blister 1	39 mm x 140 mm x 195 mm	178.00 g	1.06 dm ³
4058075267831	Shipping box 6	247 mm x 154 mm x 210 mm	1202.00 g	7.99 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.