

## PRODUCTINFORMATIEBLAD

### DALI magic

DALI magic | USB naar DALI programmeer-interface



#### Toepassingsgebieden

- Configuration of DALI ECG functions
- Monitoring of DALI installations

#### Productvoordelen

##### DALI wizard software features (included)

- Intuitive configuration of up to 64 DALI electronic control gears
- Offline / Online configuration of DALI installations
- "DALI-Spy"-functionality for recording DALI line data flow

##### Tuner4TRONIC software features

- Programming of OSRAM ECG
- Suitable for the shop floor environments
- Performs fast manual and automatic programming
- Easily enables the use of the pre-parameterization service

#### Productkenmerken

- USB DALI converter for Tuner4TRONIC and DALI wizard software for Windows PC
- Pushbutton to test DALI dimming without need of connection to computer
- Powered by USB or by included universal power supply
- Integrated automatic DALI supply of up to 64 devices (up to 4 if powered by USB)

## TECHNISCHE GEGEVENS

### ELEKTRISCHE GEGEVENS

|                   |             |
|-------------------|-------------|
| Nominale vermogen | 7,00 W      |
| Nominale spanning | 220...240 V |
| Netfrequentie     | 50/60 Hz    |

### AFMETINGEN & GEWICHT

|                                 |           |
|---------------------------------|-----------|
| Lengte                          | 120,0 mm  |
| Breedte                         | 120.00 mm |
| Breedte (incl. ronde armaturen) | 120.00 mm |
| Hoogte                          | 28.00 mm  |
| Hoogte (incl. cylin. armaturen) | 28.00 mm  |
| Product gewicht                 | 370,00 g  |

### KLEUREN & MATERIALEN

|                       |     |
|-----------------------|-----|
| Kleur van het product | Wit |
|-----------------------|-----|

### TEMPERATUREN & BEDRIJFSOMSTANDIGHEDEN

|                             |              |
|-----------------------------|--------------|
| Omgevingstemperatuur bereik | +15...+50 °C |
|-----------------------------|--------------|

### MOGELIJKHEDEN

|                  |      |
|------------------|------|
| Dimmable         | Ja   |
| Dimmer interface | DALI |

### CERTIFICATEN & NORMEN

|                   |      |
|-------------------|------|
| Veiligheidsklasse | I    |
| Type bescherming  | IP20 |

### EQUIPMENT / ACCESSORIES

- Universal power supply (100...240 V<sub>AC</sub>, 5.9 V<sub>DC</sub>, 1.15 A, EU plug)
- USB cable (male A to male B), 180 cm
- Bipolar plug for DALI connection

### DOWNLOADS

| DOWNLOADS                                                                          |                            |
|------------------------------------------------------------------------------------|----------------------------|
|  | User instruction           |
|  | Declarations of conformity |

## DOWNLOADS



CAD data 3-dim



Advertisements

## LOGISTIEKE GEGEVENS

| Productcode   | Verpakkingseenheid (stuks per verpakking) | Afmetingen (lengte x breedte x hoogte) | Brutogewicht | Volume               |
|---------------|-------------------------------------------|----------------------------------------|--------------|----------------------|
| 4052899039551 | Verzenddoos<br>1                          | 148 mm x 98 mm x 135 mm                | 376.00 g     | 1.96 dm <sup>3</sup> |

De genoemde productcodes beschrijven de kleinste hoeveelheid die besteld kan worden. Eén verzendeenheid kan bestaan uit één of meer afzonderlijke producten. Bij het plaatsen van een order enkele of veelvouden van de verpakkingseenheid invoeren.

## Referenties / Links

– Compatibele software beschikbaar via <http://www.ledvance.nl/tools>

## DISCLAIMER

Onder voorbehoud van verandering zonder kennisgeving. Fouten en drukfouten voorbehouden. Zorg ervoor dat u de meest recente versie gebruikt.