

PRODUCTINFORMATIEBLAD DALI PRO C-4RTC

DALI PRO CONT-4 RTC | Controllers voor lichtmanagementsystemen



Toepassingsgebieden

- Room control, floor control, daylight-dependent control
- Connection of light and presence sensors in DALI systems
- Conference rooms
- Offices: Individual and group workplaces
- Production and assembly facilities
- Suitable for indoor applications
- Large luminaire groups
- Industry
- Corridors
- Strip lighting
- Logistic centers
- Classrooms
- Sports halls
- Training rooms

Productvoordelen

- Easy and intuitive control via App
- Control up to 1024 DALI ECGs via LAN interconnectivity
- Plug and Play preconfigured for instant use without any startup procedure
- Mains voltage interruption buffer battery
- All the luminaires in the system can be dimmed or switched
- Simple creation of scenes and sequences
- Switching and dimming of up to 256 DALI ECGs per DALI Professional control unit
- A setpoint for daylight-dependent control can be stored by double clicking
- Sensor integration in DALI
- Remote access/remote maintenance

Productkenmerken

- Interconnection of up to 4 DALI Professional control units
- Configuration via LAN/WLAN/USB
- RGB color sequences
- Time-of-day-dependent color temperature adjustment (human centric lighting)

- Controller for 4 DALI lines
- Up to 50 pushbutton/sensor couplers can be integrated
- Integrated DALI supply
- 4 freely programmable switchover relays; load contact: 4x 5 A
- Daylight-dependent and/or presence-dependent or manual control
- Up to 4 x 16 groups can be controlled
- Integrated clock for event control
- Weekly scheduler
- Connection via push-in terminals
- Control of lighting scenes and sequences (recall/store)
- Housing for series installation
- Length of the DALI control cable: up to 300 m

TECHNISCHE GEGEVENS

ELEKTRISCHE GEGEVENS

Nominale vermogen	20,00 W
Nominale spanning	100...240 V
Netfrequentie	50...60 Hz

AFMETINGEN & GEWICHT

Lengte	90.00 mm
Breedte	160.00 mm
Breedte (incl. ronde armaturen)	160.00 mm
Hoogte	62.00 mm
Hoogte (incl. cylin. armaturen)	62.00 mm
Product gewicht	400,00 g

TEMPERATUREN & BEDRIJFSOMSTANDIGHEDEN

Omgevingstemperatuur bereik	0...+40 °C
-----------------------------	------------

MOGELIJKHEDEN

Dimmable	Nee
Dimmer interface	DALI
Aantal stuuruitgangen	4
Type montage	DIN railmontage

CERTIFICATEN & NORMEN

Keurmerken	CE
Veiligheidsklasse	I
Type bescherming	IP20

EQUIPMENT / ACCESSORIES

- Free smartphone App for iOS and Android
- Suitable for up to 256 electronic control gears with DALI interfaces
- Graphic configuration software with Windows user interface

DOWNLOADS

DOWNLOADS	
	User instruction
	User instruction

DOWNLOADS



User instruction



User instruction



Declarations of conformity



Advertisements

LOGISTIEKE GEGEVENS

Productcode	Verpakkingseenheid (stuks per verpakking)	Afmetingen (lengte x breedte x hoogte)	Brutogewicht	Volume
4008321710871	Vouwdoos 1	215 mm x 95 mm x 76 mm	440.00 g	1.55 dm ³
4008321710888	Verzenddoos 10	490 mm x 229 mm x 172 mm	4645.00 g	19.30 dm ³

De genoemde productcodes beschrijven de kleinste hoeveelheid die besteld kan worden. Eén verzendeenheid kan bestaan uit één of meer afzonderlijke producten. Bij het plaatsen van een order enkele of veelvouden van de verpakkingseenheid invoeren.

Referenties / Links

– Configuratiesoftware beschikbaar via <http://www.ledvance.nl/tools>

DISCLAIMER

Onder voorbehoud van verandering zonder kennisgeving. Fouten en drukfouten voorbehouden. Zorg ervoor dat u de meest recente versie gebruikt.