

PRODUCT DATASHEET

SMART WIFI A100 14W 230V RGBW FR E27

TRIPLE PACK

SMART+ WiFi Classic Multicolour | Classic bulb shape with WiFi technology



Areas of application

- General illumination
- Residential interiors
- Professional (hotels, bars, boutiques etc.)
- Outdoor use in suitable outdoor luminaires only

Product benefits

- Wireless control via app
- Easy to install and use
- Contains no mercury

Product features

- Controllable via LEDVANCE SMART+ WiFi App (with minimum Android™ 4.4 or iOS 10.0)
- Adjustable light color via Tunable White: Warm White to Cool White (2,700 K...6,500 K)
- RGB color control, approx. 16 million color options adjustable
- Dimmable
- Network protocol: WiFi
- Lifetime: up to 20,000 h
- Voice control works with Hey Google or Alexa


TECHNICAL DATA

Electrical data

Nominal wattage	14 W
Construction wattage	14.00 W
Nominal voltage	220...240 V
Nominal current	115 mA
Mains frequency	50/60 Hz
Power factor λ	> 0.5
Claimed equiv. conventional lamp power	100 W

Photometrical data

Light color (designation)	RGBW
Lumen main.fact.at end of nom.life time	0.95
Standard deviation of color matching	≤ 6 sdcm
Nominal luminous flux	1521 lm
Luminous flux	1521 lm
Luminous efficacy	108 lm/W
Adjustable color temperature	2700...6500 K
Color temperature	2700...6500 K
Color rendering index Ra	80
Flickering metric (Pst LM)	≤ 1
Stroboscope effect metric (SVM)	≤ 0.4



Light technical data

Beam angle	220 °
Starting time	< 0.5 s

Dimensions & Weight

Product weight	58.00 g
Diameter	70.00 mm
Maximum diameter	70 mm
Length	137.00 mm
Width	70.00 mm
Height	70.00 mm
Outer bulb [PICOS]	A70

Lifespan

Number of switching cycles	100000
Lifespan	20000 h

Colors & materials

Product color	White
Housing color	White

Temperatures & operating conditions

Ambient temperature range	-20...+40 °C
---------------------------	--------------

Additional product data

Base (standard designation)	E27
-----------------------------	-----

Capabilities

Dimmable	Yes
----------	-----

Certificates & Standards

Energy efficiency class	F
Energy consumption	14.00 kWh/1000h
Standards	CE
Type of protection	IP20

Energy labelling regulation data acc EU 2019/2015

Lighting technology used	LED
Non-directional or directional	NDLS
Mains or non-mains	MLS
Light source cap-type (or other electric interface)	E27
Connected light source (CLS)	yes
Color-tuneable light source	yes
Envelope	No
High luminance light source	No

Anti-glare shield	No
Correlated colour temperature type	RANGE
Standby power	☒ 0.5 W
Networked standby power for CLS	☒ 0.5 W
Claim of equivalent power	Yes
Chromaticity coordinate x	0.4578
Chromaticity coordinate y	0.4101
R9 Colour rendering index	>0
Beam angle correspondence	SPHERE_360
Survival factor	0.90
Displacement factor	>0.7
LED light source replaces a fluorescent light source	No
EPREL ID	1218017
Model number	AC42229

DOWNLOAD DATA

DOWNLOAD DATA	
	Declarations of conformity
	Installation guide

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075779013	Folding box 3	82 mm x 150 mm x 247 mm	355.00 g	3.04 dm ³
4058075779020	Shipping box 12	310 mm x 257 mm x 175 mm	1735.00 g	13.94 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.