

PRODUCT DATASHEET SMART+ Wifi Orbis Wall Swan 200x200mm TW

Smart+ Orbis Swan | Smart decorative wall lamp with wifi technology TW and dimmable, up and down, can be painted



Areas of application

- Indoor applications
- Kitchens, living rooms, children's rooms or home offices

Product benefits

- Easy and quick installation
- Can be painted

Product features

- Controllable via LEDVANCE SMART+ WiFi App (with minimum Android™ 4.4 or iOS 10.0)
- Controllable via voice control available: Google Assistant or Amazon Alexa
- Adjustable color temperature via Tunable White: $3,000...6,500~\mathrm{K}$
- Dimmable
- Network protocol: WiFi



TECHNICAL DATA

Electrical data

Nominal wattage	23.00 W
Nominal voltage	220240 V
Mains frequency	5060 Hz
Nominal current	96.000 mA
Inrush current	5.02 A
Power factor λ	> 0.90
Total harmonic distortion	< 20 %
Protection class	П
Operating mode	External LED driver

Photometrical data

Luminous flux	1300 lm	
Total luminous flux of contained light sources	2400 lm	
Luminous efficacy	60 lm/W	
Color temperature	30006500 K	
Light color (designation)	Tunable White	
Color rendering index Ra	> 80	
Standard deviation of color matching	< 6 sdcm	
Photobiological safety group acc. to EN62778	RG0	
Photobiological safety group acc. to EN62471	RG0	
Beam angle	360 °	

Dimensions & Weight

Length	200.00 mm
Width	200.00 mm
Height	110.00 mm
Product weight	2030.00 g

Materials & Colors

Product color	White
Housing color	White
Body material	Plaster
Cover material	Polycarbonate (PC)
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-20+40 °C	
Temperature range at storage	-20+80 °C	
Type of connection	Screw terminal	
Type of protection	IP20	
Protection class IK (shock resistance)	IK03	
Dimmable	Yes	
Type of dimming	WiFi	
Mounting type	Surface	
Mounting location	Wall	
Application environment	Indoor	
LED module replaceable	Not replaceable	
With light source	Yes	

Lifespan

Lifespan L70/B50 at 25 °C	30000 h
Number of switching cycles	15000

Emergency lighting

Integrated test switch	No
------------------------	----

Certificates & Standards

Standards	CE / UKCA
Luminaire with limited surface temperature, "D sign"	No

EQUIPMENT / ACCESSORIES

- Mounting bracket included
- Mounting screws and dowels included
- Control via app or voice control requires compatible Smart home system
- For control via LEDVANCE SMART + WiFi App, a smart phone or Tablet PC is required

DOWNLOAD DATA

	Documents and certificates
PDF	User instruction
POF	Declarations Of Conformity CE

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075574052	Folding box 1	260 mm x 172 mm x 260 mm	2248.00 g	11.63 dm³
4058075574069	Shipping box 4	362 mm x 278 mm x 538 mm	9844.00 g	54.14 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.