

PRODUCT DATASHEET

SMART+ BOLLARD Spot Panel Solar RGB + W

Smart+ Solar Spot&Bollard Multicolor | Outdoor Smart Solar Spot & Bollard



Areas of application

- Outdoor use (IP44)
- Garages
- Gardens

Product benefits

- Easy and quick installation
- Colorful garden lighting with smart and intelligent control options
- Demand based lighting and energy saving thanks to motion and daylight sensor
- High-quality materials
- Flexible mounting, also without use of ground spikes

Product features

- Controllable via LEDVANCE SMART+ App (with minimum Android 6.0 or iOS 11.0)
- Solar powered outdoor LED luminaire
- RGB color control, approx. 16 million color options adjustable
- Dimmable
- Battery charging via solar panel
- Network protocol: Bluetooth
- Type of protection: IP44
- Adjustable heads



TECHNICAL DATA

Electrical data

Nominal wattage	2x1 W
Nominal voltage	3,7 V
Nominal current	476.000 mA
Power factor λ	> 0.5
Protection class	III

Photometrical data

Luminous flux	90 lm
Total luminous flux of contained light sources	200 lm
Luminous efficacy	45 lm/W
Color temperature	3000 K
Light color (designation)	Warm White / RGB
Color rendering index Ra	> 80
Standard deviation of color matching	≤ 6 sdc _m
Flickering metric (Pst LM)	-
Stroboscope effect metric (SVM)	-

Dimensions & Weight

Diameter	48.00 mm
Height	455.00 mm
Product weight	1025.00 g



Materials & Colors

Product color	Black
Housing color	Black
Body material	Acrylonitrile butadiene styrene (ABS)
Glow Wire Test according to IEC 60695-2-12	650 °C
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-20...+40 °C
Type of protection	IP44
Dimmable	Yes
Type of dimming	Bluetooth
Mounting type	Ground spike
Application environment	Outdoor
Adjustable	Yes
LED module replaceable	Not replaceable
With light source	Yes

Lifespan

Lifespan L70/B50 at 25 °C	25000 h
Number of switching cycles	12500

Emergency lighting

Nominal voltage of battery	3.7 V
Battery charging time	8 h

Certificates & Standards

Standards	CE / UKCA
Ball shot safe	No

Additional product data

Product remark	Reset settings to default by switching the product on for three seconds and off for three seconds and repeating this five times.
----------------	--

EQUIPMENT / ACCESSORIES

– For control via LEDVANCE SMART + WiFi App, a smart phone or Tablet PC is required

DOWNLOAD DATA

Documents and certificates	
	User instruction
	Declarations Of Conformity CE

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075763708	Folding box 1	167 mm x 317 mm x 102 mm	1241.00 g	5.40 dm ³
4058075763715	Shipping box 4	350 mm x 335 mm x 232 mm	5558.00 g	27.20 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.