

PRODUCT DATASHEET

SST MR16 CCT 45 36 ° 5.6 W/2700 K/4000 K/6500 K GU5.3

LED SUPERSTAR CCT SELECT | LED SPOT with three colors in one lamp



Areas of application

- Hospitality
- Residential interiors
- Display cabinets and shop windows
- Museums, art galleries
- Shops
- Outdoor use in suitable outdoor luminaires only

Product benefits

- Low energy consumption

Product features

- Color temperature easily selectable via build-in switch
- Lifetime: up to 15,000 h
- Mercury-free lamps




TECHNICAL DATA**Electrical data**

Nominal wattage	5.6 W
Construction wattage	5.60 W
Nominal voltage	12 V
Claimed equiv. conventional lamp power	45 W
Nominal current	650 mA
Type of current	AC/DC
Inrush current	23.8 A
Operating frequency	50/60 Hz
Mains frequency	50/60 Hz
Max. lamp no. on circuit break. 10 A (B)	25
Max. lamp no. on circuit break. 16 A (B)	31
Total harmonic distortion	≤120 %
Power factor λ	> 0.50

Photometrical data

Luminous intensity	800 cd
Luminous flux	550 lm
Nominal useful luminous flux 90°	550 lm
Luminous efficacy	98 lm/W
Lumen main.fact.at end of nom.life time	0.70
Color temperature	2700 K/4000 K/6500 K
Color rendering index Ra	80
Light color	827/840/865
Standard deviation of color matching	≤6 sdcn
Rated peak intensity	800 cd
Rated LLMF at 6,000 h	0.80
Flickering metric (Pst LM)	1.0
Stroboscope effect metric (SVM)	0.4



Light technical data

Beam angle	36 °
Warm-up time (60 %)	< 0.50 s
Starting time	< 0.5 s
Rated beam angle (half peak value)	36.00 °

Dimensions & Weight



Overall length	45.00 mm
Diameter	50.00 mm
Maximum diameter	50 mm
Product weight	26.00 g

Temperatures & operating conditions

Ambient temperature range	-20...+40 °C
Maximum temperature at tc test point	78 °C

Lifespan

Lifespan	15000 h
Number of switching cycles	100000
Lumen maintenance at end of serv	0.70
Rated lamp survival factor at 6,000	≥ 0.90

Additional product data

Base (standard designation)	GU5.3
-----------------------------	-------

Mercury content	0.0 mg
Mercury-free	Yes
Product remark	All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value

Capabilities

Dimmable	No
----------	----

Certificates & Standards

Energy efficiency class	F ¹⁾
Energy consumption	6.00 kWh/1000h
Type of protection	IP20
Standards	CE / UKCA / EAC
Photobiological safety group acc. to EN62778	RG1

¹⁾ Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (lowest efficiency)

Country-specific categorizations

Order reference	LSMR1645 5,6W 1
-----------------	-----------------

LOGISTICAL DATA

Temperature range at storage	-20...+80 °C
------------------------------	--------------

Energy labelling regulation data acc EU 2019/2015

Lighting technology used	LED
Non-directional or directional	DLS
Mains or non-mains	NMLS
Light source cap-type (or other electric interface)	GU5.3
Connected light source (CLS)	No
Color-tuneable light source	No
Envelope	No
High luminance light source	No
Anti-glare shield	No
Correlated colour temperature type	STEPS
Standby power	0 W
Networked standby power for CLS	0 W

Claim of equivalent power	Yes
Length	45.00 mm
Height	50.00 mm
Width	50.00 mm
Chromaticity coordinate x	0.458
Chromaticity coordinate y	0.410
R9 Colour rendering index	1
Beam angle correspondence	NARROW_CONE_90
Survival factor	0.9
Displacement factor	/
LED light source replaces a fluorescent light source	No
EPREL ID	1382163
Model number	AC45937

DOWNLOAD DATA

Documents and certificates	
	Declarations Of Conformity CE
Photometric and lighting design files	
	Spectral power distribution

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854063978	Folding box 1	49 mm x 49 mm x 95 mm	36.00 g	0.23 dm ³
4099854063985	Shipping box 6	168 mm x 111 mm x 71 mm	288.00 g	1.32 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.