

PRODUCT DATASHEET

ST MR 16 20 36 ° 2.6 W/2700 K GU5.3

LED STAR MR16 12 V | Low-voltage LED reflector lamps MR16 with retrofit pin base



Areas of application

- Shops
- Hospitality
- Museums, art galleries
- Residential interiors
- As a downlight for marking walkways, doors, stairs, etc.
- Spotlighting for accents
- Display cabinets and shop windows
- Spotlighting heat-sensitive objects such as food, plants, etc.
- Outdoor use in suitable outdoor luminaires only

Product benefits

- Low energy consumption
- Easy replacement of halogen lamps due to compact full glass design and single optic
- Instant 100 % light, no warm-up time
- Ideal for economical spotlighting

Product features

- LED alternative to low voltage halogen lamps
- Mercury-free lamps



TECHNICAL DATA**Electrical data**

Nominal wattage	2.6 W
Construction wattage	2.60 W
Nominal voltage	12 V
Claimed equiv. conventional lamp power	20 W
Nominal current	340 mA
Type of current	AC/DC
Inrush current	18.8 A
Operating frequency	50/60 Hz
Mains frequency	50/60 Hz
Max. lamp no. on circuit break. 10 A (B)	31
Max. lamp no. on circuit break. 16 A (B)	40
Total harmonic distortion	150 %
Power factor λ	> 0.50

Photometrical data


Luminous intensity	500 cd
Luminous flux	210 lm
Nominal useful luminous flux 90°	210 lm
Luminous efficacy	80 lm/W
Lumen main.fact.at end of nom.life time	0.70
Light color (designation)	Warm White
Color temperature	2700 K
Color rendering index Ra	80
Light color	827
Standard deviation of color matching	≤6 sdcn
Rated peak intensity	500 cd
Rated LLMF at 6,000 h	0.80
Flickering metric (Pst LM)	1
Stroboscope effect metric (SVM)	0,4



Light technical data

Beam angle	36 °
Warm-up time (60 %)	< 0.50 s
Starting time	< 0.5 s
Rated beam angle (half peak value)	36.00 °

Dimensions & Weight



Overall length	44.00 mm
Diameter	50.00 mm
Maximum diameter	50 mm
Product weight	34.00 g

Temperatures & operating conditions

Ambient temperature range	-20...+40 °C
Maximum temperature at tc test point	70 °C

Lifespan

Lifespan	15000 h
Number of switching cycles	100000
Lumen maintenance at end of serv	0.70

Rated lamp survival factor at 6,000	≥ 0.90
-------------------------------------	--------

Additional product data

Base (standard designation)	GU5.3
Mercury content	0.0 mg
Mercury-free	Yes
Product remark	All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value

Capabilities

Dimmable	No
----------	----

Certificates & Standards

Energy efficiency class	F ¹⁾
Energy consumption	3.00 kWh/1000h
Type of protection	IP20
Standards	CE / UKCA / EAC
Photobiological safety group acc. to EN62778	RG1

¹⁾ Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (lowest efficiency)

Country-specific categorizations

Order reference	LED5MR162036 2,
-----------------	-----------------

LOGISTICAL DATA

Temperature range at storage	-20...+80 °C
------------------------------	--------------

Energy labelling regulation data acc EU 2019/2015

Lighting technology used	LED
Non-directional or directional	DLS
Mains or non-mains	NMLS
Light source cap-type (or other electric interface)	GU5.3
Connected light source (CLS)	No
Color-tuneable light source	No
Envelope	No
High luminance light source	No
Anti-glare shield	No

Correlated colour temperature type	SINGLE_VALUE
Standby power	0 W
Networked standby power for CLS	0.0 W
Claim of equivalent power	Yes
Length	44.00 mm
Height	50.00 mm
Width	50.00 mm
Chromaticity coordinate x	0,4578
Chromaticity coordinate y	0,4101
R9 Colour rendering index	1
Beam angle correspondence	NARROW_CONE_90
Survival factor	0,90
Displacement factor	0.00
LED light source replaces a fluorescent light source	No
EPREL ID	1235156,1368246
Model number	AC42770,AC45719

DOWNLOAD DATA

Documents and certificates



Declarations Of Conformity CE

Photometric and lighting design files



Spectral power distribution

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075796751	Folding box 1	49 mm x 49 mm x 95 mm	44.00 g	0.23 dm ³
4058075796768	Shipping box 6	168 mm x 111 mm x 71 mm	320.00 g	1.32 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

- For further products and actual information concerning LED lamps see www.ledvance.com/ledlamps
 - For Guarantee see www.ledvance.com/guarantee
 - Further information see www.ledvance.com/low-voltage-ledlamps
-

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.