

PRODUCT DATASHEET

SMART+ Wifi Undercabinet Slim 50x3.75 TW EXT

SMART+ UNDERCABINET SLIM TUNABLE WHITE | Slim Undercabinet luminaire with WIFI technology



Areas of application

- Indoor applications
- Shelf and undercabinet lighting
- Kitchens, workspaces
- Shelves

Product benefits

- Wireless control via app or voice control
- Very slim design
- Homogenous light distribution
- Easy and fast mounting on nearly every surface (adhesive tape or screws)

Product features

- Variety of combinations possible
- Provides functional or mood lighting
- Adjustable color temperature via Tunable White: 2,700...6,500 K
- Dimmable
- Available in different sizes: 50x3.75 cm, 45.7x6.5 cm, 60x6.5 cm
- 50 cm luminaire extendable with maximum two extensions of 50 cm each
- Controllable via LEDVANCE SMART+ WiFi App (with minimum Android™ 4.4 or iOS 10.0)



- Controllable via voice control available: Google Assistant or Amazon Alexa
- Network protocol: WiFi

TECHNICAL DATA**Electrical data**

Nominal wattage	8.00 W
Nominal voltage	24 V
Mains frequency	50...60 Hz
Nominal current	330.000 mA
Max. no. of lum. on circuit break. B16 A	-
Max. no. of lum. on circuit break. C10 A	-
Max. no. of lum. on circuit break. C16 A	-
Power factor λ	≥ 0.5
Protection class	III
Operating mode	Integrated LED driver

Photometrical data

Luminous flux	480 lm
Total luminous flux of contained light sources	900 lm
Luminous efficacy	60 lm/W
Color temperature	2700...6500 K
Light color (designation)	Tunable White
Color rendering index Ra	≥ 80
Standard deviation of color matching	< 6 sdcm
Photobiological safety group acc. to EN62778	RG1
Photobiological safety group acc. to EN62471	RG1
Beam angle	120 °

Dimensions & Weight

Length	500.00 mm
Width	38.00 mm
Height	8.00 mm
Product weight	230.00 g

Materials & Colors

Product color	White
Housing color	White
Body material	Aluminum Plastic
Cover material	Polycarbonate (PC)
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-20...+40 °C
Temperature range at storage	-20...+80 °C
Type of connection	Plug type C (EU)
Type of protection	IP20
Protection class IK (shock resistance)	IK03
Dimmable	Yes
Type of dimming	WiFi
Mounting type	Surface
Mounting location	Cabinet undersides
Application environment	Indoor
LED module replaceable	Not replaceable
With light source	Yes

Lifespan

Lifespan L70/B50 at 25 °C	30000 h
Number of switching cycles	15000

Emergency lighting

Luminous flux in maintained operation mode	-
--	---

Certificates & Standards

Standards	CE / ERP
Luminaire with limited surface temperature, "D sign"	No

EQUIPMENT / ACCESSORIES

- Control via app or voice control requires compatible Smart home system
- Power supply (2 m) and control box (5 cm) is included with basic version
- Extensions available in lengths: 30 cm and 50 cm
- Extensions are supplied with a connector and a connector cable (10 cm)
- Power supply and control box are not included with extensions

– For control via LEDVANCE SMART + WiFi App, a smart phone or Tablet PC is required

DOWNLOAD DATA

Documents and certificates



User instruction



Declarations Of Conformity CE

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075576292	Folding box 1	78 mm x 60 mm x 514 mm	392.00 g	2.41 dm ³
4058075576308	Shipping box 8	542 mm x 342 mm x 150 mm	3811.00 g	27.80 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.