

# PRODUCT DATASHEET Flex Audio Voice Receiver 5M RGB + RC

FLEX AUDIO WITH REMOTE CONTROL | Decorative LED Strips with warm white light and RGB for indoor use, with sound receiever and remote control



## Areas of application

- Living areas
- Indirect and direct lighting

## **Product benefits**

- Easy and quick installation

#### **Product features**

- RGB color control
- Light color: Warm White
- With behalf of integrated voice-receivers the luminaire reacts to sound and music
- Flexible, bendable LED strips

# **TECHNICAL DATA**

# Electrical data

Nominal wattage	20.00 W
Nominal voltage	220240 V
Mains frequency	5060 Hz
Nominal current	110.000 mA
Inrush current	35 mA
Power factor $\lambda$	> 0.5
Total harmonic distortion	< 100 %
Protection class	

## Photometrical data

Luminous efficacy	11 lm/W
Light color (designation)	Red / Green / Blue
Photobiological safety group acc. to EN62778	RG1
Beam angle	120 °

# Dimensions & Weight

Length	5000.00 mm
Width	10.00 mm
Height	3.00 mm
Product weight	270.00 g

## Materials & Colors

Product color	White
Housing color	White
Body material	Polyurethane (PU)
Mercury content	0.0 mg

# **Application & Mounting**

Ambient temperature range	-20+40 °C
Temperature range at storage	-2080 °C
Type of connection	Plug type C (EU)
Type of protection	IP20

Dimmable	Yes
Mounting type	Surface
Application environment	Indoor
LED module replaceable	Not replaceable

## Lifespan

Lifespan L70/B50 at 25 °C	25000 h
Number of switching cycles	10000

## Certificates & Standards

Standards	CE	

## Additional product data

Product remark	Available from July 2023

## **EQUIPMENT / ACCESSORIES**

- Complete mounting and connecting accessories included
- Remote control and battery included

## **DOWNLOAD DATA**

	Documents and certificates
PDF	User instruction

## **LOGISTICAL DATA**

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854095405	Folding box 1	70 mm x 210 mm x 200 mm	318.00 g	2.94 dm <sup>3</sup>
4099854095412	Shipping box 8	340 mm x 250 mm x 190 mm	2931.00 g	16.15 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.