

# PRODUCT DATASHEET

## Orbis IP44 Sensor 400mm 25W

ORBIS® IP44 | Splash-proof LED ceiling luminaire with sensor



---

### Areas of application

- Entrances / Hallways
- Bathrooms
- Ceiling and wall surface mounting
- Outdoor use (roofed areas) in residential sector

---

### Product benefits

- Very homogenous light
- Easy and quick installation

---

### Product features

- Ceiling luminaire with advanced LED technology
- Circular light emission
- Type of protection: IP44
- Adjustable daylight and infrared presence sensor



## TECHNICAL DATA

### Electrical data

|                                          |                     |
|------------------------------------------|---------------------|
| Nominal wattage                          | 25.00 W             |
| Nominal voltage                          | 220...240 V         |
| Mains frequency                          | 50...60 Hz          |
| Nominal current                          | 185 mA              |
| Inrush current                           | 9.1 A               |
| Max. no. of lum. on circuit break. B16 A | 18                  |
| Max. no. of lum. on circuit break. C10 A | 18                  |
| Max. no. of lum. on circuit break. C16 A | 29                  |
| Power factor $\lambda$                   | > 0.5               |
| Protection class                         | I                   |
| Operating mode                           | External LED driver |

### Photometrical data

|                                                |                      |
|------------------------------------------------|----------------------|
| Luminous flux                                  | 1800 lm              |
| Total luminous flux of contained light sources | 2700 lm              |
| Luminous efficacy                              | 80 lm/W              |
| Color temperature                              | 3000 K               |
| Light color (designation)                      | Warm White           |
| Color rendering index Ra                       | > 80                 |
| Standard deviation of color matching           | < 6 sdc <sub>m</sub> |
| Photobiological safety group acc. to EN62778   | RG1                  |
| Photobiological safety group acc. to EN62471   | RG0                  |
| Beam angle                                     | 120 °                |

### Dimensions & Weight

|                |          |
|----------------|----------|
| Diameter       | 400 mm   |
| Height         | 83.00 mm |
| Product weight | 695.00 g |

### Materials & Colors

|                |                    |
|----------------|--------------------|
| Product color  | White              |
| Housing color  | White              |
| Body material  | Aluminum           |
| Cover material | Polycarbonate (PC) |

|                 |        |
|-----------------|--------|
| Mercury content | 0.0 mg |
|-----------------|--------|

### Application & Mounting

|                                        |                             |
|----------------------------------------|-----------------------------|
| Ambient temperature range              | -20...+40 °C                |
| Temperature range at storage           | -20...+70 °C                |
| Type of connection                     | Terminal, 3-Pole (L, N, PE) |
| Type of protection                     | IP44                        |
| Protection class IK (shock resistance) | IK03                        |
| Dimmable                               | No                          |
| Mounting type                          | Surface                     |
| Mounting location                      | Ceiling                     |
| Application environment                | Indoor                      |
| LED module replaceable                 | Not replaceable             |
| With light source                      | Yes                         |

### Lifespan

|                            |         |
|----------------------------|---------|
| Lifespan L70/B50 at 25 °C  | 25000 h |
| Number of switching cycles | 12500   |

### Sensor

|                                        |                      |
|----------------------------------------|----------------------|
| Type of sensor                         | Light / Motion       |
| Sensor technology                      | Microwave            |
| Sensor detection angle                 | 125 °                |
| Detection range of motion sensor       | 14 m                 |
| Detection threshold of daylight sensor | 2 lx / 10 lx / 50 lx |

### Emergency lighting

|                                            |                |
|--------------------------------------------|----------------|
| Type of emergency light operation          | Non-maintained |
| Luminous flux in maintained operation mode | -              |
| Luminous flux in emergency operation mode  | -              |

### Certificates & Standards

|                                                      |           |
|------------------------------------------------------|-----------|
| Standards                                            | CE / UKCA |
| Luminaire with limited surface temperature, "D sign" | No        |

### EQUIPMENT / ACCESSORIES

- Complete mounting and connecting accessories included

DOWNLOAD DATA

| Documents and certificates                                                        |                               |
|-----------------------------------------------------------------------------------|-------------------------------|
|  | User instruction              |
|  | Declarations Of Conformity CE |

LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume                |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4058075651852 | Folding box<br>1             | 94 mm x 429 mm x 429 mm              | 836.00 g     | 17.30 dm <sup>3</sup> |
| 4058075651869 | Shipping box<br>5            | 482 mm x 447 mm x 459 mm             | 5129.00 g    | 98.89 dm <sup>3</sup> |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.