

PRODUCT DATASHEET

ENDURA Flood Solar 10 W 4000 K

ENDURA® FLOOD Solar Sensor | Solar-powered flood luminaire with motion and light sensor

Areas of application

- Outdoor



Product benefits

- Economical with a high light output
- Eco-friendly solar powered light
- More programable setting with PIR remote control
- Multiple adjustments of sensor range, daylight detection and hold time
- Automatically switches on and off according to available daylight thanks to photocell light sensor

Product features

- Efficient LED floodlight with high light output
- Solar powered outdoor LED luminaire
- Flexible motion and daylight sensor



TECHNICAL DATA

Electrical data


Nominal wattage	10.00 W
Nominal voltage	3,6 V
Nominal current	2700.000 mA
Protection class	III
Operating mode	Integrated LED driver

Photometrical data

Luminous flux	1200 lm
Luminous efficacy	120 lm/W
Color temperature	4000 K
Light color (designation)	Cool White
Color rendering index Ra	80
Standard deviation of color matching	< 6 sdc _m
Flickering metric (Pst LM)	-
Stroboscope effect metric (SVM)	-
Photobiological safety group acc. to EN62778	RG1
Photobiological safety group acc. to EN62471	RG1
Beam angle	95 °

Dimensions & Weight

Length	194.00 mm
Width	67.00 mm
Height	313.00 mm
Product weight	1730.00 g



Materials & Colors

Product color	Black
Housing color	Black

Body material	Metal
Glow Wire Test according to IEC 60695-2-12	650 °C
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-20...+45 °C
Type of protection	IP65
Dimmable	No
Mounting type	Surface
Application environment	Outdoor
LED module replaceable	Not replaceable
With light source	Yes

Lifespan

Lifespan L70/B50 at 25 °C	36000 h
Number of switching cycles	36000

Sensor

Type of sensor	Motion / Daylight
Sensor detection angle	95 °
Sensor controlled switching time	7 s...17 s
Detection range of motion sensor	4...8 m
Detection threshold of daylight sensor	10...30 lx

Emergency lighting

Nominal voltage of battery	3.2 V
Battery charging time	5 h

Certificates & Standards

Standards	CE / UKCA
Luminaire with limited surface temperature, "D sign"	No
Ball shot safe	No

EQUIPMENT / ACCESSORIES

- Remote control included

DOWNLOAD DATA

Documents and certificates



User instruction



Declarations Of Conformity CE

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075762350	Folding box 1	90 mm x 334 mm x 214 mm	2161.00 g	6.43 dm ³
4058075762367	Shipping box 4	384 mm x 356 mm x 245 mm	9178.00 g	33.49 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.