

# PRODUCT DATASHEET

## SMART+ Globe Camera Track & Trace

Smart+ Camera Globe Track & Trace | Outdoor Smart Camera Globe Track & Trace with E27 Base



---

### Areas of application

- Outdoor use (IP44)
- Garages
- Entrance areas

---

### Product benefits

- Easy and quick installation
- Increased perception of safety thanks to high brightness
- The recorded data is saved on the unit's memory card or cloud storage
- High-quality materials

---

### Product features

- Controllable via LEDVANCE SMART+ App (with minimum Android 6.0 or iOS 11.0)
- Controllable via voice control available: Google Assistant or Amazon Alexa
- Built in speaker and alarm siren
- HD Live view camera
- Network protocol: WiFi
- Type of protection: IP44
- Camera has Track and Trace Function to follow peoples movements
- 3 MP camera
- Talk from mobile phone to camera



- Automatic night mode
- Motion sensor with activity schedule
- Auto record of motions (SD card required)

TECHNICAL DATA

Electrical data


|                  |             |
|------------------|-------------|
| Nominal voltage  | 220...240 V |
| Mains frequency  | 50...60 Hz  |
| Protection class | II          |

Photometrical data

|                                 |   |
|---------------------------------|---|
| Flickering metric (Pst LM)      | - |
| Stroboscope effect metric (SVM) | - |

Dimensions & Weight

|                |           |
|----------------|-----------|
| Length         | 175.00 mm |
| Width          | 197.50 mm |
| Height         | 314.00 mm |
| Product weight | 1100.00 g |



Materials & Colors

|                                            |                    |
|--------------------------------------------|--------------------|
| Product color                              | Black              |
| Housing color                              | Black              |
| Body material                              | Polycarbonate (PC) |
| Glow Wire Test according to IEC 60695-2-12 | 650 °C             |
| Mercury content                            | 0.0 mg             |

Application & Mounting

|                           |                             |
|---------------------------|-----------------------------|
| Ambient temperature range | -20...+40 °C                |
| Type of connection        | Terminal, 3-Pole (L, N, PE) |
| Type of protection        | IP44                        |
| Dimmable                  | No                          |
| Mounting type             | Surface                     |
| Application environment   | Outdoor                     |

|                    |     |
|--------------------|-----|
| With light source  | No  |
| Holder designation | E27 |

### Sensor

|                                        |                   |
|----------------------------------------|-------------------|
| Type of sensor                         | Motion / Daylight |
| Sensor controlled switching time       | 60 s              |
| Detection range of motion sensor       | 3...7 m           |
| Detection threshold of daylight sensor | 0...20 lx         |

### Certificates & Standards

|                                                      |           |
|------------------------------------------------------|-----------|
| Standards                                            | CE / UKCA |
| Luminaire with limited surface temperature, "D sign" | No        |
| Ball shot safe                                       | No        |

### Additional product data

|                       |                                                                                                                                                               |
|-----------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product remark        | Maximum bulb wattage: 15 W / Reset settings to default by switching the product on for three seconds and off for three seconds and repeating this five times. |
| Number of illuminants | 1                                                                                                                                                             |

### EQUIPMENT / ACCESSORIES

- For control via LEDVANCE SMART + WiFi App, a smart phone or Tablet PC is required
- No light sources included
- Mounting screws and dowels included
- SD card not supplied
- Compatible with SD card type (SD/SDHC/SDXC)
- SD Class recommended 120-160MB/s
- Minimum card capacity 8GB/Maximum 128GB

### DOWNLOAD DATA

| Documents and certificates                                                         |                               |
|------------------------------------------------------------------------------------|-------------------------------|
|  | Declarations Of Conformity CE |

### LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume                |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4058075763425 | Folding box<br>1             | 195 mm x 220 mm x 310 mm             | 1314.00 g    | 13.30 dm <sup>3</sup> |

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume                |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4058075763432 | Shipping box<br>2            | 410 mm x 240 mm x 330 mm             | 3199.00 g    | 32.47 dm <sup>3</sup> |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.