

PRODUCT DATASHEET SMART+ WIFI COMPACT OUTDOOR PLUG EU

SMART+ Compact Outdoor Plug | Compact Outdoor Plug with smart socket to control non smart devices with WiFi technology



Areas of application

- Wherever non-smart devices need to be integrated into compatible smart home systems
- Gardens, balconies and other outdoor areas

Product benefits

- Integrates conventional electric equipment into compatible smart home systems
- Enables switching of conventional light sources and other electric devices
- Simple connection of electric devices via standard socket
- Fit for outdoor use with IP44, the protection against splash water

Product features

- Controllable via LEDVANCE SMART+ WiFi App (with minimum Android™ 4.4 or iOS 9.0)
- Controllable via voice control available: Google Assistant or Amazon Alexa
- Controllable via LEDVANCE SMART+ WiFi Remote Controller
- High switching power: up to 3,680 W / 16 A
- Network protocol: WiFi
- Type of protection: IP44
- Scheduling




TECHNICAL DATA

Electrical data

Nominal voltage	230 V
Mains frequency	50 Hz

Dimensions & Weight



Product weight	120.00 g
Diameter	57 mm
Width	57 mm
Height	98 mm

Lifespan

Number of switching cycles	100000
----------------------------	--------

Colors & materials

Product color	Anthracite
Body material	Plastic

Temperatures & operating conditions

Capabilities

Compatible smart home technology Amazon Alexa / Google Assistant	
--	--

Certificates & Standards

Protection class	I
Type of protection	IP44

EQUIPMENT / ACCESSORIES

- For control via LEDVANCE SMART+ WiFi App, a smart phone or Tablet PC is required (with minimum Android 4.4 or iOS 9.0)

Safety advice

- Disconnect devices which generate heat from the mains, i.e. from the SMART+ Plug, after use in order to avoid them being accidentally switched on.
- Very high capacitive and inductive loads may in some cases lead to destruction of the device or reduction in the number of switching cycles.
- Do not use the SMART+ Plug in conjunction with medical equipment.
- To be connected to an automatic circuit breaker (max. 16 A).

DOWNLOAD DATA

	Documents and certificates
PDF	Installation guide
PDF	Declarations Of Conformity CE

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075570979	Folding box 1	61 mm x 96 mm x 154 mm	188.00 g	0.90 dm ³
4058075570986	Shipping box 4	211 mm x 167 mm x 141 mm	964.00 g	4.97 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

EU