

PRODUCT DATASHEET NAV-T 50 W SUPER 4Y

VIALOX® NAV®-T SUPER 4Y® 50...400 W | High-pressure sodium vapor lamps for open and enclosed luminaires



Areas of application

- Streets
- Outdoor lighting
- Industrial installations
- Suitable for use in open and enclosed luminaires
- Outdoor applications only in suitable luminaires

Product benefits

- Very high luminous efficacy
- Very good luminous flux maintenance throughout the life of the lamp
- Energy savings of up to 50 % when replacing mercury vapor lamps (HQL)
- Optimum energy efficiency on POWERTRONIC® PTo 3DIM ECGs

Product features

- Lamp survival factor: 95 % after 16,000 h burning time
- Lamp maintenance factor: ≥ 80 % after 16,000 h burning time (according to DIN 13201)
- Service lifetime: 4 years (at approx. 11 h/day)
- Dimmable on conventional control gears and electronic control gears




TECHNICAL DATA

Electrical data

Nominal wattage	50 W
Construction wattage	56.00 W
Nominal voltage	86 V
Nominal current	0.75 A

Photometrical data

Luminous flux	4200 lm
Luminous efficacy	75 lm/W
Color temperature	2000 K
Color rendering index Ra	≤25
Light color	220
Rated LLMF at 2,000 h	0.92
Rated LLMF at 4,000 h	0.90
Rated LLMF at 6,000 h	0.88
Rated LLMF at 8,000 h	0.86
Rated LLMF at 12,000 h	0.84
Rated LLMF at 16,000 h	0.83
Rated LLMF at 20,000 h	0.79
UV protection	No



Dimensions & Weight

Overall length	155.00 mm
Light center length (LCL)	104,0 mm
Diameter	36,0 mm
Product weight	60.00 g

Temperatures & operating conditions

Maximum permitted outer bulb temperature	310 °C
Maximum permitted base edge temperature	210 °C

Lifespan

Lifespan	28000 h
Rated lamp survival factor at 2,000 h	0.99
Rated lamp survival factor at 4,000	0.98
Rated lamp survival factor at 6,000	0.98
Rated lamp survival factor at 8,000 h	0.97
Rated lamp survival factor at 12,000 h	0.96
Rated lamp survival factor at 16,000	0.95
Rated lamp survival factor at 20,000 h	0.85
Lifespan B10	18000 h
Lifespan B5	16000 h
Lifespan B50	28000 h

Additional product data

Base (standard designation)	E27
Mercury content	10.8 mg ¹⁾
Design / version	Clear
Product remark	Important: Before replacing for NAV Standard lamps in existing installations, check that the igniters are suitable

¹⁾ Maximum

Capabilities

Dimmable	Yes ¹⁾
Burning position	Any
Enclosed luminaire required	No

¹⁾ In combination with POWERTRONIC PTo

Certificates & Standards

Energy efficiency class	G
Energy consumption	56.00 kWh/1000h

Country-specific categorizations

ILCOS	ST-50-H/E/SL-E27-39/156
-------	-------------------------

Order reference	NAV-T 50W SUPER
-----------------	-----------------

Energy labelling regulation data acc EU 2019/2015

Lighting technology used	HPS
Non-directional or directional	NDLS
Mains or non-mains	NMLS
Light source cap-type (or other electric interface)	E27
Connected light source (CLS)	No
Color-tuneable light source	No
Envelope	SECOND
High luminance light source	No
Anti-glare shield	No
Correlated colour temperature type	SINGLE_VALUE
Claim of equivalent power	No
Length	155.00 mm
Height	36,0 mm
Width	36,0 mm
Chromaticity coordinate x	0,535
Chromaticity coordinate y	0,420
Beam angle correspondence	SPHERE_360
EPREL ID	546577
Model number	AC34369

DOWNLOAD DATA

Documents and certificates	
	User instruction
	Declarations Of Conformity CE
	Certificates
Photometric and lighting design files	
	Spectral power distribution

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4052899415379	Sleeve 1	39 mm x 39 mm x 196 mm	69.00 g	0.30 dm ³
4052899415386	Shipping box 12	168 mm x 130 mm x 212 mm	976.00 g	4.63 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.