

PRODUCT DATASHEET TruSys® ENERGY RAIL 4500 5X2,5

TruSys® ENERGY RAIL | 5-pole mounting rail

Areas of application

- Industry halls, high rack warehouse, garages, hardware stores
- Discounters, supermarkets



Product benefits

- Simple installation
- High flexibility thanks to three available lengths (1500 mm, 3000 mm, 4500 mm)
- High-value design
- Lightweight design

Product features

- Through wired with 5 core cable
- Different lenghts available
- Electrical connection internal at the first luminaire, no external connection unit required
- Anodized surface
- Rigid housing made of aluminum



TECHNICAL DATA

Electrical data

Protection class	I	
Protection class		

Dimensions & Weight

Length	4605 mm
Width	67.00 mm
Height	44 mm
Product weight	4500.00 g



Materials & Colors

Product color	Silver
Body material	Aluminum

Application & Mounting

Type of protection	IP20
Mounting location	Ceiling
With light source	Yes

Certificates & Standards

Standards	CE
Ball shot safe	No

EQUIPMENT / ACCESSORIES

- Various accessories available

DOWNLOAD DATA

Documents and certificates
 User instruction

Documents and certificates



Declarations Of Conformity CE

CAD/BIM files



BIM_Revit_3D

Tender texts



Tender documents

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075100336	BAG 1	4,615 mm x 72 mm x 56 mm	5070.00 g	18.61 dm ³
4058075100343	Shipping box 2	4,615 mm x 149 mm x 64 mm	11040.00 g	44.01 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.