

## PRODUCT DATASHEET

### BASE CLAS B 40 FR 4.9 W/2700 K E14

LED BASE CLASSIC B | LED lamps, classic mini-candle shape



#### Areas of application

- General illumination
- Domestic applications
- Chandeliers
- Outdoor use in suitable outdoor luminaires only

#### Product benefits

- Lower thermal output (compared with the standard reference product)
- Very low energy consumption
- Shockproof and vibration-proof thanks to LED technology
- No UV and near-IR radiation in the light beam
- Instant 100 % light, no warm-up time
- Simple direct replacement for conventional incandescent lamps

#### Product features

- Professional LED lamps for line voltage
- Not suitable for use with dimmers
- Good color rendering ( $R_a \geq 80$ ) and color stability throughout the life of the lamp
- Base: E14, B22d
- Mercury-free lamps



TECHNICAL DATA

Electrical data

|                                          |             |
|------------------------------------------|-------------|
| Nominal wattage                          | 4.9 W       |
| Construction wattage                     | 4.90 W      |
| Nominal voltage                          | 220...240 V |
| Claimed equiv. conventional lamp power   | 40 W        |
| Nominal current                          | 47 mA       |
| Type of current                          | AC          |
| Inrush current                           | 3 A         |
| Operating frequency                      | 50...60 Hz  |
| Mains frequency                          | 50...60 Hz  |
| Max. lamp no. on circuit break. 10 A (B) | 45          |
| Max. lamp no. on circuit break. 16 A (B) | 70          |
| Power factor $\lambda$                   | > 0.50      |

Photometrical data


|                                         |            |
|-----------------------------------------|------------|
| Luminous flux                           | 470 lm     |
| Nominal useful luminous flux 90°        | 470 lm     |
| Luminous efficacy                       | 95 lm/W    |
| Lumen main.fact.at end of nom.life time | 0.93       |
| Light color (designation)               | Warm White |
| Color temperature                       | 2700 K     |
| Color rendering index Ra                | ≥80        |
| Light color                             | 827        |
| Standard deviation of color matching    | ≤6 sdcm    |
| Rated LLMF at 6,000 h                   | 0.80       |
| Flickering metric (Pst LM)              | 1.0        |
| Stroboscope effect metric (SVM)         | 0.4        |



Light technical data

|                                    |          |
|------------------------------------|----------|
| Beam angle                         | 200 °    |
| Warm-up time (60 %)                | < 0.50 s |
| Starting time                      | < 0.5 s  |
| Rated beam angle (half peak value) | 200.00 ° |

Dimensions & Weight



|                  |          |
|------------------|----------|
| Overall length   | 96.00 mm |
| Diameter         | 37.00 mm |
| Maximum diameter | 37 mm    |
| Product weight   | 16.00 g  |

Temperatures & operating conditions

|                                      |              |
|--------------------------------------|--------------|
| Ambient temperature range            | -20...+40 °C |
| Maximum temperature at tc test point | 79 °C        |

Lifespan

|                                     |         |
|-------------------------------------|---------|
| Lifespan                            | 10000 h |
| Number of switching cycles          | 100000  |
| Lumen maintenance at end of serv    | 0.93    |
| Rated lamp survival factor at 6,000 | ≥ 0.90  |

Additional product data

|                             |        |
|-----------------------------|--------|
| Base (standard designation) | E14    |
| Mercury content             | 0.0 mg |
| Mercury-free                | Yes    |

|                  |                                                                                                                                                                                                                                                                                                                                              |
|------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Design / version | Frosted                                                                                                                                                                                                                                                                                                                                      |
| Product remark   | All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value |

### Capabilities

|          |    |
|----------|----|
| Dimmable | No |
|----------|----|

### Certificates & Standards

|                                              |                                     |
|----------------------------------------------|-------------------------------------|
| Energy efficiency class                      | F <sup>1)</sup>                     |
| Energy consumption                           | 5.00 kWh/1000h                      |
| Type of protection                           | IP20                                |
| Standards                                    | CE / LVD / EMC / SLR / ROHS / REACH |
| Photobiological safety group acc. to EN62778 | RG0                                 |

<sup>1)</sup> Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (lowest efficiency)

### Country-specific categorizations

|                 |                            |
|-----------------|----------------------------|
| ILCOS           | DRBB/F-5,7-220-240-E14-106 |
| Order reference | BASECLB40 4,9W/            |

### LOGISTICAL DATA

|                              |              |
|------------------------------|--------------|
| Temperature range at storage | -20...+80 °C |
|------------------------------|--------------|

### Energy labelling regulation data acc EU 2019/2015

|                                                     |              |
|-----------------------------------------------------|--------------|
| Lighting technology used                            | LED          |
| Non-directional or directional                      | NDLS         |
| Mains or non-mains                                  | MLS          |
| Light source cap-type (or other electric interface) | E14          |
| Connected light source (CLS)                        | No           |
| Color-tuneable light source                         | No           |
| Envelope                                            | No           |
| High luminance light source                         | No           |
| Anti-glare shield                                   | No           |
| Correlated colour temperature type                  | SINGLE_VALUE |
| Standby power                                       | 0.00 W       |
| Networked standby power for CLS                     | 0.00 W       |

|                                                      |                         |
|------------------------------------------------------|-------------------------|
| Claim of equivalent power                            | Yes                     |
| Length                                               | 96.00 mm                |
| Height                                               | 37.00 mm                |
| Width                                                | 37.00 mm                |
| Chromaticity coordinate x                            | 0.4578                  |
| Chromaticity coordinate y                            | 0.4101                  |
| R9 Colour rendering index                            | >0                      |
| Beam angle correspondence                            | SPHERE_360              |
| Survival factor                                      | 0.90                    |
| Displacement factor                                  | N/A                     |
| LED light source replaces a fluorescent light source | No                      |
| EPREL ID                                             | 1403231,523316,1351514  |
| Model number                                         | AC31158,AC45012,AC24717 |

## DOWNLOAD DATA

| Documents and certificates                                                          |                               |
|-------------------------------------------------------------------------------------|-------------------------------|
|    | Declarations Of Conformity CE |
| Photometric and lighting design files                                               |                               |
|  | Spectral power distribution   |

## LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume               |
|---------------|------------------------------|--------------------------------------|--------------|----------------------|
| 4058075184411 | Folding box<br>5             | 36 mm x 177 mm x 107 mm              | 100.00 g     | 0.68 dm <sup>3</sup> |
| 4058075184428 | Shipping box<br>50           | 372 mm x 186 mm x 121 mm             | 1200.00 g    | 8.37 dm <sup>3</sup> |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.