

# PRODUCT DATASHEET

## ENDURA Classic Post 55cm E27

ENDURA® CLASSIC POST | Stainless steel luminaires with glass diffuser



---

### Areas of application

- Outdoor use (IP44)
- Building facades
- Entrance lighting
- Patios, balconies
- Pathway lighting
- Driveways

---

### Product benefits

- High flexibility in the choice of the light source thanks to E27 base
- Suitable for smart applications thanks to compatibility with Smart + lamps from LEDVANCE
- Easy and quick installation

---

### Product features

- Stainless steel housing
- Diffuser made of clear glass with hammer finish
- Available with and without motion sensor
- Available as wall and bollard luminaires




TECHNICAL DATA

Electrical data

|                  |               |
|------------------|---------------|
| Nominal voltage  | 220...240 V   |
| Mains frequency  | 50...60 Hz    |
| Protection class | I             |
| Operating mode   | Mains voltage |

Dimensions & Weight

|                |           |
|----------------|-----------|
| Diameter       | 127.00 mm |
| Height         | 550.00 mm |
| Product weight | 1300.00 g |



Materials & Colors

|                 |                 |
|-----------------|-----------------|
| Product color   | Steel           |
| Housing color   | Steel           |
| Body material   | Stainless steel |
| Mercury content | 0.0 mg          |

Application & Mounting

|                              |                |
|------------------------------|----------------|
| Ambient temperature range    | -20...+40 °C   |
| Temperature range at storage | -20...+85 °C   |
| Type of connection           | Screw terminal |
| Type of protection           | IP44           |

|                         |          |
|-------------------------|----------|
| Dimmable                | No       |
| Mounting type           | Standing |
| Mounting location       | Floor    |
| Application environment | Outdoor  |
| With light source       | No       |
| Holder designation      | E27      |

### Certificates & Standards

|           |                 |
|-----------|-----------------|
| Standards | CE / EAC / UKCA |
|-----------|-----------------|

### Additional product data

|                       |                            |
|-----------------------|----------------------------|
| Product remark        | Maximum bulb wattage: 60 W |
| Number of illuminants | 1                          |

### EQUIPMENT / ACCESSORIES

- Complete mounting and connecting accessories included
- No light sources included

### DOWNLOAD DATA

| Documents and certificates                                                         |                               |
|------------------------------------------------------------------------------------|-------------------------------|
|  | User instruction              |
|  | Packaging insert              |
|  | Declarations Of Conformity CE |

### LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume                |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4058075206564 | Folding box<br>1             | 154 mm x 154 mm x 576 mm             | 1358.00 g    | 13.66 dm <sup>3</sup> |
| 4058075206571 | Shipping box<br>4            | 589 mm x 322 mm x 326 mm             | 5885.00 g    | 61.83 dm <sup>3</sup> |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.