

# PRODUCT DATASHEET

## ENDURA PRO Flood Sensor 15W 4000K IP55

### Dark Gray

ENDURA® PRO FLOOD SENSOR | High efficiency wall sensor luminaires with wide beam angle in innovative optical design



---

#### Areas of application

- Outdoor
- Parking lots, city squares, parks
- Arcade passage

---

#### Product benefits

- Homogenous illumination
- Lighting according to requirements due to adjustable luminaire head
- Easy and quick installation

---

#### Product features

- 4 operating modes selectable (light 6h continuous on, standby, switch-on by movement or dusk)
- Adjustable luminaire head
- Type of protection: IP55
- Impact resistance: IK05
- Protection class: II



TECHNICAL DATA

Electrical data


|                                          |               |
|------------------------------------------|---------------|
| Nominal wattage                          | 15.00 W       |
| Nominal voltage                          | 220...240 V   |
| Mains frequency                          | 50...60 Hz    |
| Nominal current                          | 8000.000 mA   |
| Inrush current                           | 8 A           |
| Inrush current time T <sub>h50</sub>     | 50 µs         |
| Max. no. of lum. on circuit break. B16 A | 94            |
| Max. no. of lum. on circuit break. C10 A | 75            |
| Max. no. of lum. on circuit break. C16 A | 120           |
| Power factor λ                           | > 0.88        |
| Protection class                         | II            |
| Operating mode                           | Mains voltage |

Photometrical data

|                                                |                     |
|------------------------------------------------|---------------------|
| Luminous flux                                  | 1500 lm             |
| Total luminous flux of contained light sources | 1980 lm             |
| Luminous efficacy                              | 100 lm/W            |
| Color temperature                              | 4000 K              |
| Light color (designation)                      | Cool White          |
| Color rendering index Ra                       | ≥80                 |
| Standard deviation of color matching           | ≤6 sdc <sub>m</sub> |
| Flickering metric (Pst LM)                     | <=1                 |
| Stroboscope effect metric (SVM)                | <=0.9               |
| Photobiological safety group acc. to EN62778   | RG1                 |
| Photobiological safety group acc. to EN62471   | RG1                 |
| Beam angle                                     | 100 °               |

Dimensions & Weight

|                |           |
|----------------|-----------|
| Length         | 151.00 mm |
| Width          | 56.00 mm  |
| Height         | 205.00 mm |
| Product weight | 365.00 g  |



Materials & Colors

|                 |                    |
|-----------------|--------------------|
| Product color   | Dark grey          |
| Housing color   | Dark gray          |
| Body material   | Polycarbonate (PC) |
| Cover material  | Polycarbonate (PC) |
| Mercury content | 0.0 mg             |

Application & Mounting

|                                        |                             |
|----------------------------------------|-----------------------------|
| Ambient temperature range              | -20...+40 °C                |
| Temperature range at storage           | -25...+70 °C                |
| Type of connection                     | Terminal, 3-Pole (L, N, PE) |
| Type of protection                     | IP55                        |
| Protection class IK (shock resistance) | IK05                        |
| Dimmable                               | No                          |
| Mounting type                          | Surface                     |
| Mounting location                      | Wall                        |
| Application environment                | Outdoor                     |
| LED module replaceable                 | Not replaceable             |
| With light source                      | Yes                         |

Lifespan

|                            |         |
|----------------------------|---------|
| Lifespan L70/B50 at 25 °C  | 30000 h |
| Number of switching cycles | 12500   |

Control gear

|                |              |
|----------------|--------------|
| Output current | 205...260 mA |
|----------------|--------------|

Sensor

|                                        |                        |
|----------------------------------------|------------------------|
| Type of sensor                         | Light / Motion         |
| Sensor technology                      | Passive infrared (PIR) |
| Sensor detection angle                 | 180 °                  |
| Sensor controlled switching time       | 2 s...15 min           |
| Detection range of motion sensor       | 12 m                   |
| Detection threshold of daylight sensor | 1...1000 lx            |

Certificates & Standards

|                                                      |                 |
|------------------------------------------------------|-----------------|
| Standards                                            | CE / EAC / UKCA |
| Luminaire with limited surface temperature, "D sign" | No              |

DOWNLOAD DATA

| Documents and certificates                                                        |                               |
|-----------------------------------------------------------------------------------|-------------------------------|
|  | User instruction              |
|  | Declarations Of Conformity CE |

LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume                |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4058075228801 | Folding box<br>1             | 68 mm x 158 mm x 214 mm              | 418.00 g     | 2.30 dm <sup>3</sup>  |
| 4058075228818 | Shipping box<br>6            | 326 mm x 213 mm x 231 mm             | 3273.00 g    | 16.04 dm <sup>3</sup> |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.