

RefLED Superia Retro MR16

RefLED Superia Retro MR16 V2 345LM 830 36° SL

0029227



Product features

- Compact, energy efficient and exceptional value for money product
- Same shape and size as halogen MR16 lamp
- Compact Cluster SMD technology enabling high efficiency with halogen look
- Reduced visible heat sink from the front
- Available in 36 degree
- High lumen efficacy
- 12V AC/DC
- 25,000 hours average rated life
- 3 years warranty



PRODUCT OVERVIEW

Product name	RefLED Superia Retro MR16 V2 345LM 830 36° SL
Technology	LED
Watt (Rated) (W)	4.3
Type	LED exchangeable
Cap/Base	GU5.3
Fixture rating	Open
General application	Education, Hospitality, Residential & Consumer
ETIM Class	EC001959
E-number FI	4741107
Warranty	3 years
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Colour Consistency (SDCM)	6
Beam Angle (°)	36
Photobiological Risk Group	RG1
Wattage (W)	4.3
Product Voltage (V)	12
Dimmable	No
Average life (Nominal) (h)	25000
Product EAN number	5410288292274

DATA TABLE

General data

Product name	RefLED Superia Retro MR16 V2 345LM 830 36° SL
Technology	LED
Watt (Rated) (W)	4.3
Type	LED exchangeable
Cap/Base	GU5.3
Fixture rating	Open

RefLED Superia Retro MR16

RefLED Superia Retro MR16 V2 345LM 830 36° SL

0029227

General application	Education, Hospitality, Residential & Consumer
Operating temperature range (°C)	-20°C...+40°C
Performance ambient temperature Tq (°C)	25
ETIM Class	EC001959
E-number FI	4741107
Warranty	3 years

Optical data

Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Colour Consistency (SDCM)	6
Luminous Intensity (cd)	600
Beam Angle (°)	36
Photobiological Risk Group	RG1
Lumen maintenance at end of nominal life (%)	70

Electrical data

Wattage (W)	4.3
Equivalent watt (W)	35
Product Voltage (V)	12
Control gear required	No
No. Of switching cycles before premature failures	>50000
Transformer required	Yes
Dimmable	No
Lamp Energy Label (class)	F

Lifetime data

Lifespan L70 B50	25000
Average life (Nominal) (h)	25000
Average life (Rated) (h)	25000

Physical data

Nominal Product Length (mm)	44
Nominal Product Diameter (mm)	50
Weight (kg)	0.032

Packaging

Single packaging type	Carton
Product EAN number	5410288292274
Packaging single length / height (cm)	6.1
Packaging single width (cm)	5.1
Packaging single depth (cm)	8.2
DUN14 (inner)	25410288292278
Units per inner package	6
Packaging inner length / height (cm)	19.6

RefLED Superia Retro MR16


RefLED Superia Retro MR16 V2 345LM 830 36° SL
0029227

Packaging inner width (cm)	11.2
Packaging inner depth (cm)	9.4
DUN14 (outer)	15410288292271
Units per outer package	36
Packaging outer length / height (cm)	35.5
Packaging outer width (cm)	21.4
Packaging outer depth (cm)	22.0


Safety data

Optimal operating condition (°C)	-20-40
Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Dry applications use only	Yes
Suitable for household illumination	Yes
Safety message	Not Suitable for totally enclosed fixtures

PHOTOMETRY



TECHNICAL DRAWINGS




RefLED Superia Retro MR16
RefLED Superia Retro MR16 V2 345LM 830 36° SL
0029227

**ENERG**

SYLVANIA

0029227




5
kWh/1000h



2019/2015

RefLED Superia Retro MR16
RefLED Superia Retro MR16 V2 345LM 830 36° SL
0029227


SYLVANIA
0029227



5
kWh/1000h

