

ToLEDo GLS

ToLEDo GLS V6 1521LM 840 E27 SL

0027966



Product features

- Compact and elegant design
- Suitable replacement for halogen, incandescent and compact fluorescent GLS lamps
- Instant light at the flick of a switch
- Uniform light distribution
- Good colour rendering (CRI 80)
- Perfect for hotels, restaurants, lobbies, corridors, stairwells, reception areas
- Lower maintenance costs
- A+ energy rating



PRODUCT OVERVIEW

Product name	ToLEDo GLS V6 1521LM 840 E27 SL
Technology	LED
Watt (Rated) (W)	14
Type	ToLEDo GLS
Cap/Base	E27
Fixture rating	Open
General application	Hospitality, Residential & Consumer
ETIM Class	EC001959
E-number FI	4740567
Warranty	3 years
Luminous flux (lm)	1521
Colour temperature (K)	4000
Light colour	Cool White
CRI (Ra)	80
Beam Angle (°)	180
Wattage (W)	14
Product Voltage (V)	230
Average life (Nominal) (h)	15000
Product EAN number	5410288279664

DATA TABLE

General data

Product name	ToLEDo GLS V6 1521LM 840 E27 SL
Technology	LED
Watt (Rated) (W)	14
Type	ToLEDo GLS
Cap/Base	E27
Fixture rating	Open
General application	Hospitality, Residential & Consumer
Performance ambient temperature Tq (°C)	25
ETIM Class	EC001959

ToLEDo GLS

ToLEDo GLS V6 1521LM 840 E27 SL

0027966

E-number FI	4740567
Warranty	3 years

Optical data

Luminous flux (lm)	1521
Luminous flux (Rated) (lm)	1521
Colour temperature (K)	4000
Light colour	Cool White
CRI (Ra)	80
Beam Angle (°)	180
Lumen maintenance at end of nominal life (%)	70

Electrical data

Wattage (W)	14
Equivalent watt (W)	100
Starting time (max) (s)	0.5
Warm-up time to 60% of full light (max) (s)	1
Product Voltage (V)	230
Lamp power factor	0.5
No. Of switching cycles before premature failures	>50000
Inrush Current (A)	5.25
Nominal Frequency (Hz)	50/60Hz
Max. Luminaires per 10A C Breaker	78
Max. Luminaires per 16A C Breaker	126
Max. Luminaires per 20A C Breaker	158

Lifetime data

Average life (Nominal) (h)	15000
Average life (Rated) (h)	15000

Physical data

Nominal Product Length (mm)	120
Nominal Product Diameter (mm)	60
Weight (kg)	0.056

Packaging

Single packaging type	Carton
Product EAN number	5410288279664
Packaging single length / height (cm)	11.3
Packaging single width (cm)	6.4
Packaging single depth (cm)	6.4
DUN14 (inner)	25410288279668
Units per inner package	6
Packaging inner length / height (cm)	20.4
Packaging inner width (cm)	13.4
Packaging inner depth (cm)	13.7
DUN14 (outer)	15410288279661

ToLEDo GLS
ToLEDo GLS V6 1521LM 840 E27 SL
0027966

Units per outer package	60
Packaging outer length / height (cm)	72.4
Packaging outer width (cm)	22.2
Packaging outer depth (cm)	29.7

Safety data

Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Dry applications use only	Yes
Suitable for household illumination	Yes
Safety message	Not Suitable for totally enclosed fixtures