

TOLEDO CANDLE
ToLEDo CANDLE V6 806LM 865 E14 SL
0028339



- Product features**
- Compact and elegant design• Suitable replacement for halogen, incandescent and compact fluorescent candle lamps• Instant light at the flick of a switch• Uniform light distribution• Good colour rendering (CRI 80)• Perfect for hotels, restaurants, lobbies, corridors, stairwells, reception areas• Lower maintenance costs• A+ energy rating



PRODUCT OVERVIEW

Product name	ToLEDo CANDLE V6 806LM 865 E14 SL
Technology	LED
Watt (Rated) (W)	8
Cap/Base	E14
Fixture rating	Open
General application	Hospitality, Residential & Consumer
ETIM Class	EC001959
Warranty	3 years
Luminous flux (lm)	806
Colour temperature (K)	6500
Light colour	Daylight
CRI (Ra)	80
Beam Angle (°)	180
Wattage (W)	8
Product Voltage (V)	230
Average life (Nominal) (h)	15000
Product EAN number	5410288283395

DATA TABLE

General data	
Product name	ToLEDo CANDLE V6 806LM 865 E14 SL
Technology	LED
Watt (Rated) (W)	8
Cap/Base	E14
Fixture rating	Open
General application	Hospitality, Residential & Consumer
Performance ambient temperature Tq (°C)	25
ETIM Class	EC001959
Warranty	3 years
Optical data	
Luminous flux (lm)	806

TOLEDO CANDLE

ToLEDo CANDLE V6 806LM 865 E14 SL

0028339

Luminous flux (Rated) (lm)	806
Colour temperature (K)	6500
Light colour	Daylight
CRI (Ra)	80
Beam Angle (°)	180
Lumen maintenance at end of nominal life (%)	70

Electrical data

Wattage (W)	8
Equivalent watt (W)	60
Starting time (max) (s)	0.5
Warm-up time to 60% of full light (max) (s)	1
Product Voltage (V)	230
Lamp power factor	0.5
No. Of switching cycles before premature failures	>50000
Inrush Current (A)	2.7
Nominal Frequency (Hz)	50/60Hz
Max. Luminaires per 10A C Breaker	131
Max. Luminaires per 16A C Breaker	211
Max. Luminaires per 20A C Breaker	364

Lifetime data

Average life (Nominal) (h)	15000
Average life (Rated) (h)	15000

Physical data

Nominal Product Length (mm)	115
Nominal Product Diameter (mm)	39
Weight (kg)	0.031

Packaging

Single packaging type	Carton
Product EAN number	5410288283395
Packaging single length / height (cm)	3.9
Packaging single width (cm)	3.9
Packaging single depth (cm)	11.6
DUN14 (inner)	25410288283399
Units per inner package	6
DUN14 (outer)	15410288283392
Units per outer package	6
Packaging outer length / height (cm)	12.5
Packaging outer width (cm)	8.5
Packaging outer depth (cm)	12.3

Safety data

Breakage cleaning instructions	Not applicable
Special purpose lamp	No



TOLEDO CANDLE
ToLEDo CANDLE V6 806LM 865 E14 SL
0028339

Dry applications use only	Yes
Suitable for household illumination	Yes
Safety message	Not Suitable for totally enclosed fixtures