

## RefLED ES50

RefLED ES50 V6 320LM 830 110 SL10

0029173



### Product features

- Compact, energy efficient and exceptional value LED GU10 lamp
- Same shape and size as halogen GU10 lamp
- Compact Cluster SMD technology enabling high efficiency with halogen look
- Reduced visible heat sink from the front
- Available in 110 degree beam angle
- High lumen efficacy
- 15,000 hours average rated life
- 3 years warranty



## PRODUCT OVERVIEW

|                                 |                                                                                     |
|---------------------------------|-------------------------------------------------------------------------------------|
| Product name                    | RefLED ES50 V6 320LM 830 110 SL10                                                   |
| Technology                      | LED                                                                                 |
| Watt (Rated) (W)                | 4.2                                                                                 |
| Type                            | LED exchangeable                                                                    |
| Cap/Base                        | GU10                                                                                |
| Fixture rating                  | Open                                                                                |
| General application             | Education, Hospitality, Museums & Galleries, Office, Residential & Consumer, Retail |
| ETIM Class                      | EC001959                                                                            |
| Warranty                        | 3 years                                                                             |
| Colour temperature (K)          | 3000                                                                                |
| Light colour                    | Warm White                                                                          |
| CRI (Ra)                        | 80                                                                                  |
| Colour Variation Initial (SDCM) | SDCM6                                                                               |
| Colour Consistency (SDCM)       | 6                                                                                   |
| Beam Angle (°)                  | 110                                                                                 |
| Photobiological Risk Group      | RG1                                                                                 |
| Wattage (W)                     | 4.2                                                                                 |
| Product Voltage (V)             | 230                                                                                 |
| Dimmable                        | No                                                                                  |
| Average life (Nominal) (h)      | 15000                                                                               |
| Product EAN number              | 5410288291734                                                                       |

## DATA TABLE

### General data

|                  |                                   |
|------------------|-----------------------------------|
| Product name     | RefLED ES50 V6 320LM 830 110 SL10 |
| Technology       | LED                               |
| Watt (Rated) (W) | 4.2                               |
| Type             | LED exchangeable                  |
| Cap/Base         | GU10                              |

## RefLED ES50

RefLED ES50 V6 320LM 830 110 SL 10

0029173

|                                         |                                                                                     |
|-----------------------------------------|-------------------------------------------------------------------------------------|
| Fixture rating                          | Open                                                                                |
| General application                     | Education, Hospitality, Museums & Galleries, Office, Residential & Consumer, Retail |
| Operating temperature range (°C)        | -20°C...+40°C                                                                       |
| Performance ambient temperature Tq (°C) | 25                                                                                  |
| ETIM Class                              | EC001959                                                                            |
| Warranty                                | 3 years                                                                             |

### Optical data

|                                              |            |
|----------------------------------------------|------------|
| Colour temperature (K)                       | 3000       |
| Light colour                                 | Warm White |
| CRI (Ra)                                     | 80         |
| Colour Variation Initial (SDCM)              | SDCM6      |
| Colour Consistency (SDCM)                    | 6          |
| Luminous Intensity (cd)                      | 170        |
| Beam Angle (°)                               | 110        |
| Photobiological Risk Group                   | RG1        |
| Lumen maintenance at end of nominal life (%) | 70         |

### Electrical data

|                                                   |         |
|---------------------------------------------------|---------|
| Wattage (W)                                       | 4.2     |
| Equivalent watt (W)                               | 45      |
| Product Voltage (V)                               | 230     |
| Control gear required                             | No      |
| No. Of switching cycles before premature failures | >50000  |
| Transformer required                              | No      |
| Dimmable                                          | No      |
| Inrush Current (A)                                | 3.9     |
| Inrush Duration (µs)                              | 4100    |
| Lamp Energy Label (class)                         | F       |
| Nominal Frequency (Hz)                            | 50/60Hz |
| Max. Luminaires per 16A C Breaker                 | 123     |
| Max. Luminaires per 16A B Breaker                 | 74      |

### Lifetime data

|                            |       |
|----------------------------|-------|
| Lifespan L70 B50           | 15000 |
| Average life (Nominal) (h) | 15000 |
| Average life (Rated) (h)   | 15000 |

### Physical data

|                               |      |
|-------------------------------|------|
| Nominal Product Height (mm)   | 54   |
| Nominal Product Diameter (mm) | 50   |
| Weight (kg)                   | 0.35 |

### Packaging

|                       |               |
|-----------------------|---------------|
| Single packaging type | Carton        |
| Product EAN number    | 5410288291734 |


RefLED ES50  
RefLED ES50 V6 320LM 830 110 SL 10  
0029173

|                                       |                |
|---------------------------------------|----------------|
| Packaging single length / height (cm) | 8.2            |
| Packaging single width (cm)           | 19.5           |
| Packaging single depth (cm)           | 10.4           |
| DUN14 (outer)                         | 15410288291731 |
| Units per outer package               | 6              |
| Packaging outer length / height (cm)  | 9.2            |
| Packaging outer width (cm)            | 40.3           |
| Packaging outer depth (cm)            | 32.7           |


Safety data

|                                     |                                            |
|-------------------------------------|--------------------------------------------|
| Optimal operating condition (°C)    | -20-40                                     |
| Breakage cleaning instructions      | Not applicable                             |
| Special purpose lamp                | No                                         |
| Dry applications use only           | Yes                                        |
| Suitable for household illumination | Yes                                        |
| Safety message                      | Not Suitable for totally enclosed fixtures |

PHOTOMETRY



TECHNICAL DRAWINGS




RefLED ES50  
RefLED ES50 V6 320LM 830 110 SL 10  
0029173

**ENERG**

**SYLVANIA**

0029173



**5**  
kWh/1000h




2019/2015

RefLED ES50  
RefLED ES50 V6 320LM 830 110 SL 10  
0029173



0029173



5  
kWh/1000h



2019/2015