

### RefLED R50 REFLED R50 V3 470LM 865 E14 SL 0026335



#### **Product features**

• Energy efficient LED alternative for traditional incandescent and halogen blown reflector lamp• Modern construction and attractive design• Mercury free solution• Long average rated lifetime: 15,000 hours• Lower maintenance cost compared to traditional lamps• Non-dimmable• 3 years warranty• Perfect for general lighting applications: residential lighting, down lights, hotels, hotels, restaurants, bars, lobbies, corridors, halls, etc











### PRODUCT OVERVIEW

Product name	REFLED R50 V3 470LM 865 E14 SL
Technology	LED
Watt (Rated) (W)	5
Cap/Base	E14
Fixture rating	Open
General application	Hospitality, Residential & Consumer
ETIM Class	EC001959
E-number FI	4740800
Warranty	3 years
Colour temperature (K)	6500
Light colour	Daylight
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Colour Consistency (SDCM)	6
Beam Angle (°)	120
Wattage (W)	5
Product Voltage (V)	230
Dimmable	No
Average life (Nominal) (h)	15000
Product EAN number	5410288263359

### **DATA TABLE**

General data	
Product name	REFLED R50 V3 470LM 865 E14 SL
Technology	LED
Watt (Rated) (W)	5
Cap/Base	E14
Fixture rating	Open
General application	Hospitality, Residential & Consumer
Performance ambient temperature Tq (°C)	25
ETIM Class	EC001959
E-number FI	4740800
Warranty	3 years



# RefLED R50 REFLED R50 V3 470LM 865 E14 SL 0026335

Optical data	
Colour temperature (K)	6500
Light colour	Daylight
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Colour Consistency (SDCM)	6
Luminous Intensity (cd)	136
Beam Angle (°)	120
Electrical data	
Wattage (W)	5
Starting time (max) (s)	0.5
Warm-up time to 60% of full light (max) (s)	2
Mains voltage (V)	220-240V
Product Voltage (V)	230
Lamp power factor	0.5
No. Of switching cycles before premature failures	>50000
Dimmable	No
Nominal Frequency (Hz)	50/60Hz
Lifetime data	
Average life (Nominal) (h)	15000
Average life (Rated) (h)	15000
Dhysical data	
Physical data	
Nominal Product Length (mm)	83
Nominal Product Diameter (mm)	50
Weight (kg)	0.024
Packaging	
5 5	Onder
Single packaging type Product EAN number	Carton 5410288263359
	5.0
Packaging single width (cm)	5.0
Packaging single depth (cm)	7.8
Packaging single depth (cm) DUN14 (outer)	7.6 15410288263356
Units per outer package	6
Packaging outer length / height (cm)	15.6
Packaging outer width (cm)	10.8
Packaging outer depth (cm)	8.8
Salety data	
Safety data  Breakage cleaning instructions	Not applicable
Breakage cleaning instructions	Not applicable
Breakage cleaning instructions Special purpose lamp	No
Breakage cleaning instructions	



## RefLED R50 REFLED R50 V3 470LM 865 E14 SL 0026335

Safety message

Not Suitable for totally enclosed fixtures