

Isoline DALI

ISOLINE 3380MM 4K 1.7WD 1.7BLK DA
0042555



Product features

- Isoline LED linear luminaire for industrial and commercial applications. 3380mm length with 1.7m blank section, with wide optics provide homogenous light distribution for open areas. Suitable for DALI Dimming. Aluminium housing, RAL 9016. Max + 35 °C operating temperature range, 4000 K, CRI 80, UGR <25, 3 SDCM. 57W power consumption, 8150lm luminous flux, 146 lm/W efficacy, 3380 mm x 62 mm x 59 mm (L x W x H) dimensions, IP20, IK03, 220-240 V 50/60 Hz, Class I. Lifespan L70:B50 60,000 hours.



PRODUCT OVERVIEW

Product name	ISOLINE 3380MM 4K 1.7WD 1.7BLK DA
Technology	LED
Housing	Aluminium
Mount	Suspended
Fixture rating	Enclosed
General application	Logistics & Industry
ETIM Class	EC000986
Warranty	5 years
Fixture luminous flux (lm)	8150
Luminous flux (lm)	8150
Luminaire efficacy (lm/W)	145
Colour temperature (K)	4000
Colour Code	840
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Beam Angle (°)	90
Glare control	< 25
Photobiological Risk Group	RG1
Total power consumption (W)	56
Electrical protection	Class I
Control gear type	LED driver constant current
Dimmable	Yes
Dimming method	DALI
Minimum dimming level (%)	1
LED Flickering Rate	Ultra low (5% or less)
Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP20
IK rating	IK03
Product EAN number	5410288425559

Isoline DALI

ISOLINE 3380MM 4K 1.7WD 1.7BLK DA
0042555

DATA TABLE

General data

Product name	ISOLINE 3380MM 4K 1.7WD 1.7BLK DA
Technology	LED
Housing	Aluminium
Mount	Suspended
Fixture rating	Enclosed
General application	Logistics & Industry
Operating temperature range (°C)	0°C...+35°C
ETIM Class	EC000986
Warranty	5 years

Optical data

Fixture luminous flux (lm)	8150
Luminous flux (lm)	8150
Luminaire efficacy (lm/W)	145
Colour temperature (K)	4000
Colour Code	840
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Beam Angle (°)	90
Glare control	< 25
Photobiological Risk Group	RG1

Electrical data

Total power consumption (W)	56
Mains voltage (V)	220-240V
THD (at 230 V, 50 Hz, full load, at 100% dimming level) xx.x %	5.5
Electrical protection	Class I
Control gear required	No
Control gear type	LED driver constant current
Dimmable	Yes
Dimming method	DALI
Minimum dimming level (%)	1
Drive current (mA)	250
Inrush Current (A)	28
Glow Wire Test (°C)	650
Energy Efficiency Class (A->G) of contained light source	C
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Ultra low (5% or less)
Max. Luminaires per 10A B Breaker	14
Max. Luminaires per 16A B Breaker	23

Lifetime data

Lifespan L70 B50	60000
------------------	-------

Isoline DALI

ISOLINE 3380MM 4K 1.7WD 1.7BLK DA
0042555

Lifespan L80 B10	60000
Lifespan L90 B10	31500


Physical data

Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP20
IK rating	IK03
IK rating of sensor	IK03
Diffuser finish	Transparent
Diffuser material	PMMA Acrylic
Nominal Product Length (mm)	3380
Nominal Product Width (mm)	62
Nominal Product Height (mm)	59
Weight (kg)	5.0

Packaging

Single packaging type	Mix(80% carton, 20% plastic)
Product EAN number	5410288425559
Packaging single length / height (cm)	353.0
Packaging single width (cm)	6.5
Packaging single depth (cm)	5.8
DUN14 (outer)	05410288425559
Units per outer package	1
Packaging outer length / height (cm)	353.0
Packaging outer width (cm)	6.5
Packaging outer depth (cm)	5.8

PHOTOMETRY



TECHNICAL DRAWINGS

