

Isoline
ISOLINE 3380MM 4K 1.7ASYR 1.7BLK
0042562



Product features

- Isoline LED linear luminaire for industrial and commercial applications. 3380mm length with 1.7m blank section, with asymmetrical (Right) optics provide homogenous light distribution for aisles and focus areas. Aluminium housing, RAL 9016. Max + 35 °C operating temperature range, 4000 K, CRI 80, 3 SDCM. 57W power consumption, 8000lm luminous flux, 140 lm/W efficacy, 3380 mm x62 mm x 59 mm (L x W x H) dimensions, IP20, IK03, 220-240 V 50/60 Hz, Class I. Lifespan L70:B50 60,000 hours.



PRODUCT OVERVIEW

Product name	ISOLINE 3380MM 4K 1.7ASYR 1.7BLK
Technology	LED
Housing	Aluminium
Mount	Suspended
Fixture rating	Enclosed
General application	Logistics & Industry
ETIM Class	EC000986
Warranty	5 years
Fixture luminous flux (lm)	8000
Luminous flux (lm)	8000
Luminaire efficacy (lm/W)	140
Colour temperature (K)	4000
Colour Code	840
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Photobiological Risk Group	RG1
Total power consumption (W)	57
Electrical protection	Class I
Control gear type	LED driver constant current
Dimmable	No
Dimming method	N/A
LED Flickering Rate	Ultra low (5% or less)
Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP20
IK rating	IK03
Product EAN number	5410288425627

DATA TABLE

General data	
Product name	ISOLINE 3380MM 4K 1.7ASYR 1.7BLK

Isoline

ISOLINE 3380MM 4K 1.7ASYR 1.7BLK
0042562

Technology	LED
Housing	Aluminium
Mount	Suspended
Fixture rating	Enclosed
General application	Logistics & Industry
Operating temperature range (°C)	0°C...+35°C
ETIM Class	EC000986
Warranty	5 years

Optical data

Fixture luminous flux (lm)	8000
Luminous flux (lm)	8000
Luminaire efficacy (lm/W)	140
Colour temperature (K)	4000
Colour Code	840
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Photobiological Risk Group	RG1

Electrical data

Total power consumption (W)	57
Mains voltage (V)	220-240V
Lamp power factor	0.95
THD (at 230 V, 50 Hz, full load, at 100% dimming level) xx.x %	10
Electrical protection	Class I
Control gear required	No
Control gear type	LED driver constant current
Dimmable	No
Dimming method	N/A
Drive current (mA)	250
Inrush Current (A)	25
Inrush Duration (µs)	250
Glow Wire Test (°C)	650
Energy Efficiency Class (A->G) of contained light source	C
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Ultra low (5% or less)
Max. Luminaires per 10A C Breaker	27
Max. Luminaires per 13A C Breaker	35
Max. Luminaires per 16A C Breaker	45
Max. Luminaires per 20A C Breaker	58
Max. Luminaires per 10A B Breaker	16
Max. Luminaires per 13A B Breaker	21
Max. Luminaires per 16A B Breaker	27
Max. Luminaires per 20A B Breaker	35

Lifetime data

Lifespan L70 B50	60000
------------------	-------

Isoline

ISOLINE 3380MM 4K 1.7ASYR 1.7BLK
0042562

Lifespan L80 B10	60000
Lifespan L90 B10	31500


Physical data

Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP20
IK rating	IK03
IK rating of sensor	IK03
Diffuser finish	Transparent
Diffuser material	PMMA Acrylic
Nominal Product Length (mm)	3380
Nominal Product Width (mm)	62
Nominal Product Height (mm)	59
Weight (kg)	5.0

Packaging

Single packaging type	Mix(80% carton, 20% plastic)
Product EAN number	5410288425627
Packaging single length / height (cm)	353.0
Packaging single width (cm)	6.5
Packaging single depth (cm)	5.8
DUN14 (outer)	05410288425627
Units per outer package	1
Packaging outer length / height (cm)	353.0
Packaging outer width (cm)	6.5
Packaging outer depth (cm)	5.8

PHOTOMETRY



TECHNICAL DRAWINGS

