

ToLEDo Retro Candle

ToLEDo RT CANDLE V4 CL 250LM 827 E14 SL

0027180



Product features

- Perfect for decorative and general lighting applications and creates a warm ambience similar to traditional lamps
- The versatile ToLEDo Retro candle range is the ideal replacement for halogen and incandescent lamps and perfect for chandeliers and decorative applications
- Same look, size and functionality as incandescent lamps
- Omni-directional light distribution
- A++ energy rating
- Gives same sparkling light effect as the incandescent lamp
- Dimensionally identical to incandescent lamps - fits all fixtures
- Environment-friendly - no mercury and lower CO2 emissions



PRODUCT OVERVIEW

Product name	ToLEDo RT CANDLE V4 CL 250LM 827 E14 SL
Technology	LED
Watt (Rated) (W)	2.5
Type	ToLEDo Retro Candle
Cap/Base	E14
Fixture rating	Open
General application	Hospitality, Residential & Consumer
ETIM Class	EC001959
E-number FI	4740289
E-number SE	8290511
Warranty	3 years
Luminous flux (lm)	250
Colour temperature (K)	2700
Light colour	Homelight
CRI (Ra)	80
Beam Angle (°)	300
Wattage (W)	2.5
Product Voltage (V)	230
Average life (Nominal) (h)	15000
Product EAN number	5410288271804

DATA TABLE

General data

Product name	ToLEDo RT CANDLE V4 CL 250LM 827 E14 SL
Technology	LED
Watt (Rated) (W)	2.5
Type	ToLEDo Retro Candle
Cap/Base	E14
Fixture rating	Open
General application	Hospitality, Residential & Consumer

ToLEDo Retro Candle

ToLEDo RT CANDLE V4 CL 250LM 827 E14 SL
0027180

Performance ambient temperature Tq (°C) 25

ETIM Class EC001959

E-number FI 4740289

E-number SE 8290511

Warranty 3 years

Optical data

Luminous flux (lm) 250

Luminous flux (Rated) (lm) 250

Colour temperature (K) 2700

Light colour Homelight

CRI (Ra) 80

Beam Angle (°) 300

Lumen maintenance at end of nominal life (%) 70

Electrical data

Wattage (W) 2.5

Equivalent watt (W) 25

Starting time (max) (s) 0.5

Warm-up time to 60% of full light (max) (s) 1

Product Voltage (V) 230

Lamp power factor 0.5

No. Of switching cycles before premature failures >50000

Inrush Current (A) 1.2

Nominal Frequency (Hz) 50/60Hz

Max. Luminaires per 10A C Breaker 83

Max. Luminaires per 16A C Breaker 133

Max. Luminaires per 20A C Breaker 167

Lifetime data

Average life (Nominal) (h) 15000

Average life (Rated) (h) 15000

Physical data

Nominal Product Length (mm) 97

Nominal Product Diameter (mm) 35

Weight (kg) 0.014

Packaging

Single packaging type Carton

Product EAN number 5410288271804

Packaging single length / height (cm) 10.8

Packaging single width (cm) 4.2

Packaging single depth (cm) 4.2

DUN14 (inner) 25410288271808

Units per inner package 6

ToLEDo Retro Candle
ToLEDo RT CANDLE V4 CL 250LM 827 E14 SL
0027180

Packaging inner length / height (cm)	13.4
Packaging inner width (cm)	9.0
Packaging inner depth (cm)	12.1
DUN14 (outer)	15410288271801
Units per outer package	60
Packaging outer length / height (cm)	49.0
Packaging outer width (cm)	29.7
Packaging outer depth (cm)	15.2

Safety data	
Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Dry applications use only	Yes
Suitable for household illumination	Yes
Safety message	Not Suitable for totally enclosed fixtures

TECHNICAL DRAWINGS

