


SylSafe EXIT Mod
SylSafe Exit-Mod EX V EM3 MT MS
0041755



Product features

- SylSafe Exit-Mod EX V EM3 MT MS is a ceiling mounted emergency exit sign. Comes with ISO7010 compliant legend pack. Arrows left, right, up, down and a blank sheet for single sided versions. EC legend pack is available as accessory. Viewing distance 26m. White housing colour. Maintained 3hr emergency operation with NiMH rechargeable battery. Recharge period 24 hours. 4.9W, IK03, IP20. Power Factor 0.49. Class II electrical construction.



PRODUCT OVERVIEW

Product name	SylSafe Exit-Mod EX V EM3 MT MS
Technology	LED
Type	LED
Mount	Ceiling surface mounting
General application	Office, Hospitality, Retail, Museums & Galleries, Education, Logistics & Industry
ETIM Class	EC001957
Warranty	5 years
Fixture luminous flux (lm)	-
Light source included	INTEGRATED LED
Electrical protection	Class II
Housing colour	White
IP rating	IP20
IK rating	IK03
Product EAN number	5410288417554

DATA TABLE

General data	
Product name	SylSafe Exit-Mod EX V EM3 MT MS
Technology	LED
Type	LED
Mount	Ceiling surface mounting
General application	Office, Hospitality, Retail, Museums & Galleries, Education, Logistics & Industry
ETIM Class	EC001957
Warranty	5 years
Optical data	
Fixture luminous flux (lm)	-
Emergency duration (h)	3
Electrical data	
Light source included	INTEGRATED LED
Mains voltage (V)	230-240V

SylSafe EXIT Mod

SylSafe Exit-Mod EX V EM3 MT MS

0041755

Lamp power factor	0.49
Electrical protection	Class II
Control gear required	Yes
Drive current (mA)	60
Nominal Frequency (Hz)	50/60Hz

Physical data

Housing colour	White
IP rating	IP20
IK rating	IK03
Nominal Product Length (mm)	300
Nominal Product Width (mm)	57
Nominal Product Height (mm)	253
Weight (kg)	0.866

Packaging

Single packaging type	Carton
Product EAN number	5410288417554
Packaging single length / height (cm)	31.0
Packaging single width (cm)	22.6
Packaging single depth (cm)	4.4
DUN14 (outer)	05410288417554
Units per outer package	1
Packaging outer length / height (cm)	31.0
Packaging outer width (cm)	22.6
Packaging outer depth (cm)	4.4

TECHNICAL DRAWINGS

