


Start Surface IP66 Ø350mm Emergency
START SURFACE IP66 1450LM 830 EM3 IK10 WHT
0049008



Product features

- LED exterior surface mounted luminaire, 350mm diameter, 1450lm as max. lumen output, 14W max. power consumption, 104lm/W efficacy, 3000K color temperature, CRI80, IP66, IK10, 50,000 hours (L70), white housing, vandal resistant. Integrated emergency, 3 hours, supplied with anti-theft screws



PRODUCT OVERVIEW

Product name	START SURFACE IP66 1450LM 830 EM3 IK10 WHT
Technology	LED
Cap/Base	N/A
Housing	PC Polycarbonate
Mount	Ceiling surface mounting
Environment	Indoor, Outdoor
General application	Hospitality
ETIM Class	EC002892
Warranty	5 years
Fixture luminous flux (lm)	1450
Luminaire efficacy (lm/W)	85
LOR (%)	100
Colour temperature (K)	3000
Colour Code	830
Light colour	Warm White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Beam Angle (°)	120
Glare control	< 25
Photobiological Risk Group	RG0
Luminous flux (emergency) (lm)	124
Total power consumption (W)	17
Electrical protection	Class II
Control gear type	LED driver constant current
Control gear mounting	Integrated
Dimmable	No
Dimming method	N/A
LED Flickering Rate	Ultra low (5% or less)
Housing colour	RAL 9003 - Signal white
IP rating	IP66
IK rating	IK10
Product EAN number	5410288490083

Start Surface IP66 Ø350mm Emergency START SURFACE IP66 1450LM 830 EM3 IK10 WHT 0049008

DATA TABLE

General data

Product name	START SURFACE IP66 1450LM 830 EM3 IK10 WHT
Technology	LED
Cap/Base	N/A
Housing	PC Polycarbonate
Mount	Ceiling surface mounting
Environment	Indoor, Outdoor
General application	Hospitality
Operating temperature range (°C)	0°C...+25°C
Performance ambient temperature Tq (°C)	25
ETIM Class	EC002892
Warranty	5 years

Optical data

Fixture luminous flux (lm)	1450
Luminaire efficacy (lm/W)	85
LOR (%)	100
Colour temperature (K)	3000
Colour Code	830
Light colour	Warm White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Adjustable chromaticity	N
Beam Angle (°)	120
Glare control	< 25
Photobiological Risk Group	RG0
Lumen maintenance at end of nominal life (%)	70
Luminous flux (emergency) (lm)	124
Emergency duration (h)	3

Electrical data

Total power consumption (W)	17
Mains voltage (V)	220-240V
Lamp power factor	1
THD (at 230 V, 50 Hz, full load, at 100% dimming level) xx.x %	15
Electrical protection	Class II
Control gear required	No
Control gear type	LED driver constant current
Control gear mounting	Integrated
Dimmable	No
Dimming method	N/A
Drive current (mA)	350
Inrush Current (A)	5
Inrush Duration (µs)	100

Start Surface IP66 Ø350mm Emergency *START SURFACE IP66 1450LM 830 EM3 IK10 WHT* 0049008

Energy Efficiency Class (A->G) of contained light source	D
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Ultra low (5% or less)
Max. Luminaires per 10A C Breaker	90
Max. Luminaires per 13A C Breaker	117
Max. Luminaires per 16A C Breaker	144
Max. Luminaires per 20A C Breaker	180
Max. Luminaires per 10A B Breaker	72
Max. Luminaires per 13A B Breaker	93
Max. Luminaires per 16A B Breaker	115
Max. Luminaires per 20A B Breaker	144

Lifetime data

Lifespan L70 B50	50000
------------------	-------

Physical data

Housing colour	RAL 9003 - Signal white
IP rating	IP66
IK rating	IK10
Diffuser finish	Opal
Diffuser material	PC Polycarbonate
Nominal Product Length (mm)	350
Nominal Product Width (mm)	350
Nominal Product Height (mm)	111
Nominal Product Diameter (mm)	350
Weight (kg)	1.4

Packaging





Single packaging type	Carton
Product EAN number	5410288490083
Packaging single length / height (cm)	40.0
Packaging single width (cm)	40.0
Packaging single depth (cm)	11.0
DUN14 (outer)	05410288490083
Units per outer package	1
Packaging outer length / height (cm)	40.0
Packaging outer width (cm)	40.0
Packaging outer depth (cm)	11.0

Safety data

Optimal operating condition (°C)	0-25
----------------------------------	------

PHOTOMETRY

Start Surface IP66 Ø350mm Emergency
START SURFACE IP66 1450LM 830 EM3 IK10 WHT
0049008



TECHNICAL DRAWINGS

