

ToLEDo Retro G120
ToLEDo RT G125 V5 CL 1521LM 827 E27 SL
0029546



Product features

- Perfect for decorative and general lighting applications and creates a warm ambiance similar to traditional lampsSame look, size and functionality as incandescent lampsOmni-directional light distributionSuitable replacement for incandescent and halogen lampsGives same sparkling light effect as incandescent lampDimensionally identical to incandescent lamps - fits all fixturesEnvironment friendly - no mercury and lower CO2 emissions



PRODUCT OVERVIEW

Product name	ToLEDo RT G125 V5 CL 1521LM 827 E27 SL
Technology	LED
Watt (Rated) (W)	11
Type	LED exchangeable
Cap/Base	E27
Fixture rating	Open
General application	Hospitality, Residential & Consumer
ETIM Class	EC001959
E-number FI	4740963
Warranty	3 years
Luminous flux (lm)	1521
Colour temperature (K)	2700
Light colour	Homelight
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Photobiological Risk Group	RG1
Wattage (W)	11
Product Voltage (V)	230
Dimmable	No
Average life (Nominal) (h)	15000
Product EAN number	5410288295466

DATA TABLE

General data

Product name	ToLEDo RT G125 V5 CL 1521LM 827 E27 SL
Technology	LED
Watt (Rated) (W)	11
Type	LED exchangeable
Cap/Base	E27
Fixture rating	Open
General application	Hospitality, Residential & Consumer

ToLEDo Retro G120

ToLEDo RT G125 V5 CL 1521LM 827 E27 SL

0029546

Operating temperature range (°C)	-20°C...+40°C
Performance ambient temperature Tq (°C)	25
ETIM Class	EC001959
E-number FI	4740963
Warranty	3 years

Optical data

Luminous flux (lm)	1521
Luminous flux (Rated) (lm)	1521
Colour temperature (K)	2700
Light colour	Homelight
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Photobiological Risk Group	RG1
Lumen maintenance at end of nominal life (%)	70

Electrical data

Wattage (W)	11
Equivalent watt (W)	100
Product Voltage (V)	230
Control gear required	No
No. Of switching cycles before premature failures	>50000
Transformer required	No
Dimmable	No
Inrush Current (A)	5.93
Inrush Duration (µs)	180
Lamp Energy Label (class)	D
Nominal Frequency (Hz)	50/60Hz
Max. Luminaires per 16A C Breaker	27
Max. Luminaires per 16A B Breaker	13

Lifetime data

Lifespan L70 B50	15000
Average life (Nominal) (h)	15000
Average life (Rated) (h)	15000

Physical data

Nominal Product Length (mm)	178
Nominal Product Diameter (mm)	125
Weight (kg)	0.135

Packaging


Single packaging type	Carton
Product EAN number	5410288295466
Packaging single length / height (cm)	19.0
Packaging single width (cm)	13.0
Packaging single depth (cm)	13.0

ToLEDo Retro G120
ToLEDo RT G125 V5 CL 1521LM 827 E27 SL
0029546


DUN14 (outer)	15410288295463
Units per outer package	6
Packaging outer length / height (cm)	20.0
Packaging outer width (cm)	80.3
Packaging outer depth (cm)	13.5

Safety data	
Optimal operating condition (°C)	-20-40
Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Dry applications use only	Yes
Suitable for household illumination	Yes
Safety message	Not Suitable for totally enclosed fixtures

PHOTOMETRY



TECHNICAL DRAWINGS




ToLEDo Retro G120
ToLEDo RT G125 V5 CL 1521LM 827 E27 SL
0029546



ENERG

SYLVANIA

0029546




11
kWh/1000h



2019/2015

ToLEDo Retro G120
ToLEDo RT G125 V5 CL 1521LM 827 E27 SL
0029546

**ENERG**
SYLVANIA
0029546



11
kWh/1000h



2019/2015