



- 











Product name	START Waterproof Tubular 1200 IP66 4300lm 830 PC
Technology	LED
General application	Logistics & Industry
ETIM Class	EC000109
Warranty	5 years
Fixture luminous flux (lm)	4250
Luminaire efficacy (lm/W)	121
Colour temperature (K)	3000
CRI (Ra)	80
Beam Angle (°)	120
Photobiological Risk Group	RG1
Total power consumption (W)	35
Electrical protection	Class I
Dimmable	No
Dimming method	N/A
IP rating	IP66
IK rating	IK10
Product EAN number	5410288471501

DATA TABLE

General data

Product name	START Waterproof Tubular 1200 IP66 4300lm 830 PC
Technology	LED
General application	Logistics & Industry
Operating temperature range (°C)	-25°C...+50°C
Performance ambient temperature Tq (°C)	25
ETIM Class	EC000109
Warranty	5 years

Optical data

Fixture luminous flux (lm)	4250
Luminaire efficacy (lm/W)	121

START Waterproof Tubular IP66

START Waterproof Tubular 1200 IP66 4300lm 830 PC

0047150

Colour temperature (K)	3000
CRI (Ra)	80
Beam Angle (°)	120
Photobiological Risk Group	RG1

Electrical data

Total power consumption (W)	35
Mains voltage (V)	220-240V
Lamp power factor	0.95
THD (at 230 V, 50 Hz, full load, at 100% dimming level) xx.x %	10
Electrical protection	Class I
Dimmable	No
Dimming method	N/A
Drive current (mA)	250
Inrush Current (A)	30
Inrush Duration (µs)	200
Glow Wire Test (°C)	650
Energy Efficiency Class (A->G) of contained light source	E
Nominal Frequency (Hz)	50/60Hz
Max. Luminaires per 10A C Breaker	20
Max. Luminaires per 13A C Breaker	26
Max. Luminaires per 16A C Breaker	32
Max. Luminaires per 20A C Breaker	40
Max. Luminaires per 10A B Breaker	12
Max. Luminaires per 13A B Breaker	15
Max. Luminaires per 16A B Breaker	19
Max. Luminaires per 20A B Breaker	24

Lifetime data

Lifespan L70 B50	90000
Lifespan L70 B20	90000
Lifespan L70 B10	90000
Lifespan L80 B50	90000
Lifespan L80 B20	85000
Lifespan L80 B10	78000
Lifespan L90 B50	48000
Lifespan L90 B20	41000
Lifespan L90 B10	37000

Physical data

IP rating	IP66
IK rating	IK10
Nominal Product Length (mm)	1195
Nominal Product Width (mm)	70
Nominal Product Height (mm)	70
Weight (kg)	2.5

START Waterproof Tubular IP66

START Waterproof Tubular 1200 IP66 4300lm 830 PC

0047150


Packaging

Single packaging type	Carton
Product EAN number	5410288471501
Packaging single length / height (cm)	133.5
Packaging single width (cm)	10.5
Packaging single depth (cm)	10.5
DUN14 (outer)	15410288471508
Units per outer package	2
Packaging outer length / height (cm)	135.0
Packaging outer width (cm)	23.0
Packaging outer depth (cm)	23.0

Safety data

Optimal operating condition (°C)	-25-50
----------------------------------	--------

PHOTOMETRY



Distance [m]	Cone diameter [m]	Beam angle [°]	Illuminance [lx]
0.5	1.41	54.8°	4533
1.0	2.81	54.8°	1131
1.5	4.22	54.8°	503
2.0	5.63	54.8°	250
2.5	7.04	54.8°	131
3.0	8.44	54.8°	70

Distance [m] Cone diameter [m] Illuminance [lx]
 C0 - C180 (Half beam angle: 132.0°)
 C90 - C270 (Half beam angle: 109.2°)

TECHNICAL DRAWINGS

