

Optix Linear Surface 1200 Direct-Indirect

OPTIX LINEAR SURFACE 1200 DI LUMI 4K ALU

2023857



Product features

- OPTIX LINEAR SURFACE 1200 D/I LUMI 4000K ALU is a suspended linear luminaire for office and education applications with Aluminised plastic extra low glare optics and RAL9016 colour fixture body. Constant current driver. 4000K Neutral White LED, chromaticity tolerance of 3-step MacAdam ellipse. For 4000K - Colour rendering index Ra >98; Melanopic Ratio MEER: 0.784; Fidelity Index R_f: 93; Gamut Index R_g: 98. For 4000K luminous flux: 4000lm. Power consumption: 36W. Luminaire efficacy: 111lm/W. UGR<16 Luminance at 65°<200 Cd/m², IK07, IP20. Photobiological safety risk group 0. Electrical protection Class I. Glow wire test 850°C. 60,000hrs L80B20 lifespan.



PRODUCT OVERVIEW

Product name	OPTIX LINEAR SURFACE 1200 DI LUMI 4K ALU
Technology	LED LumiNature
Cap/Base	N/A
Housing	Steel
Mount	Ceiling surface mounting
Fixture rating	Enclosed
General application	Education, Office
ETIM Class	EC002892
Warranty	5 years
Fixture luminous flux (lm)	4020
Luminaire efficacy (lm/W)	112
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	98
Colour Variation Initial (SDCM)	SDCM3
Colour Consistency (SDCM)	3
Glare control	< 16
Photobiological Risk Group	RG1
Total power consumption (W)	36
Electrical protection	Class I
Control gear type	LED driver constant current
Dimmable	No
Dimming method	N/A
Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP20
IK rating	IK07
Product EAN number	5025768238576

DATA TABLE

General data

Product name	OPTIX LINEAR SURFACE 1200 DI LUMI 4K ALU
Technology	LED LumiNature

Optix Linear Surface 1200 Direct-Indirect

OPTIX LINEAR SURFACE 1200 DI LUMI 4K ALU

2023857

Cap/Base	N/A
Housing	Steel
Mount	Ceiling surface mounting
Fixture rating	Enclosed
General application	Education, Office
Performance ambient temperature Tq (°C)	25
ETIM Class	EC002892
Warranty	5 years

Optical data

Fixture luminous flux (lm)	4020
Luminaire efficacy (lm/W)	112
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	98
Colour Variation Initial (SDCM)	SDCM3
Colour Consistency (SDCM)	3
Glare control	< 16
Photobiological Risk Group	RG1

Electrical data

Total power consumption (W)	36
Mains voltage (V)	220-240V
Lamp power factor	0.95
Electrical protection	Class I
Control gear required	No
Control gear type	LED driver constant current
Transformer required	No
Dimmable	No
Dimming method	N/A
Drive current (mA)	250
Inrush Current (A)	30
Inrush Duration (µs)	250
Glow Wire Test (°C)	850
Energy Efficiency Class (A->G) of contained light source	F, F(more than 1 Light Source)
Nominal Frequency (Hz)	50/60Hz
Max. Luminaires per 10A C Breaker	15
Max. Luminaires per 13A C Breaker	22
Max. Luminaires per 16A C Breaker	29
Max. Luminaires per 20A C Breaker	35
Max. Luminaires per 10A B Breaker	8
Max. Luminaires per 13A B Breaker	11
Max. Luminaires per 16A B Breaker	15
Max. Luminaires per 20A B Breaker	18

Lifetime data

Lifespan L70 B50	100000
Lifespan L80 B20	60000

Optix Linear Surface 1200 Direct-Indirect

OPTIX LINEAR SURFACE 1200 DI LUMI 4K ALU

2023857



Physical data

Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP20
IK rating	IK07
Diffuser finish	Matt/satinized
Diffuser material	PC Polycarbonate
Nominal Product Length (mm)	1129
Nominal Product Width (mm)	90
Nominal Product Height (mm)	80
Weight (kg)	3.5

Packaging

Single packaging type	Carton
Product EAN number	5025768238576
Packaging single length / height (cm)	119.0
Packaging single width (cm)	10.0
Packaging single depth (cm)	11.0
DUN14 (outer)	05025768238576
Units per outer package	1
Packaging outer length / height (cm)	119.0
Packaging outer width (cm)	10.0
Packaging outer depth (cm)	11.0

PHOTOMETRY



TECHNICAL DRAWINGS

