

Insaver HE Topper LED 150 PIR INSAVER 150 HE TOPPER LED NW PIR PLUS3 3033925

Product features



Insaver HE Topper is a ceiling recessed LED downlight with integrated PIR sensor with time (up to 8 mins) and daylight lux level settings. Die-cast aluminium body, Non dimmable LED driver, 8W, 800lm, 100lm/W, 4000K, shallow recessed depth of 55mm. Wieland GST compatible



PRODUCT OVERVIEW

Product name	INSAVER 150 HE TOPPER LED NW PIR PLUS3
Technology	LED
Housing	Aluminium
Mount	Ceiling recessed mounting
Environment	External
General application	Hospitality, Logistics & Industry, Office
ETIM Class	EC001744
Warranty	3 years
Fixture luminous flux (Im)	800
Luminaire efficacy (Im/W)	100
LOR (%)	100
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Beam Angle (°)	64
Total power consumption (W)	8
Electrical protection	Class II
Control gear type	Electronic ballast
Dimming method	N/A
Housing colour	White
IP rating	IP44/20
IK rating	IK02
Product EAN number	8711971339250

DATA TABLE

General data	
Product name	INSAVER 150 HE TOPPER LED NW PIR PLUS3
Technology	LED
Housing	Aluminium
Mount	Ceiling recessed mounting
Environment	External
General application	Hospitality, Logistics & Industry, Office



Insaver HE Topper LED 150 PIR INSAVER 150 HE TOPPER LED NW PIR PLUS3 3033925

Optical data	ETIM Class	EC001744
Pixture luminous flux (lm)		
Fixture luminous flux (Im)	· · · · · · · · · · · · · · · · · · ·	3,00.0
Luminaire efficacy (lm/W)	Optical data	
Lumlaire efficacy (lm/W) 100 LOR (%) 100 Colour temperature (K) 4000 Light colour Neutral White CRI (Ra) 80 Adjustable chromaticity N Beam Angle (*) 64 Electrical data *** Total power consumption (W) 8 Mains voltage (Y) 220-240V Electrical protection Class II Control gear type Electronic ballast Transformer required Yes Dimming method N/A Drive current (mA) 350 Glow Wire Test (*C) 650 Energy Efficiency Class (A->G) of contained light source E Physical data Housing colour White IP rating IK02 Diffuser finish Opal Diffuser material PC Polycarbonate Reflector finish Other Nominal Product Length (mm) 165 Nominal Product Diameter (mm) 165 Nominal Product Diameter (mm) 16	Fixture luminous flux (lm)	800
LOR (%)	• •	100
Colour temperature (K) 4000 Light colour Neutral White CRI (Ra) 80 Adjustable chromaticity N Beam Angle (*) 64 Electrical data **** Total power consumption (W) 8 Mains voltage (V) 220-240V Electrical protection Class II Control gear type Electronic ballast Transformer required Yes Dimming method N/A Drive current (mA) 350 Glow Wire Test (*C) 650 Energy Efficiency Class (A>G) of contained light source E Physical data Housing colour White IP rating IP44/20 IIK rating IK02 Diffuser finish Opal Diffuser material PC Polycarbonate Reflector finish Other Nominal Product Width (mm) 165 Nominal Product Height (mm) 55 Nominal Product Diameter (mm) 165 Veight (kg) 0.7 <	• • •	100
Light colour Neutral White CRI (Ra) 80 Adjustable chromaticity N Beam Angle (*) 64 Electrical data	• •	4000
Adjustable chromaticity N Beam Angle (*) 64 Electrical data		Neutral White
Adjustable chromaticity N Beam Angle (*) 64 Electrical data	CRI (Ra)	80
Electrical data Total power consumption (W) 8 Mains voltage (V) 220-240V Electrolar protection Class II Control gear type Electronic ballast Transformer required Yes Dimming method N/A Drive current (mA) 350 Glow Wire Test (*C') 650 Energy Efficiency Class (A->G) of contained light source Physical data Housing colour White IP rating IP44/20 IK rating IRV02 Diffuser finish Opal Diffuser material PC Polycarbonate Reflector finish Other Nominal Product Length (mm) 165 Nominal Product Ublemeter (mm) 165 Nominal Product Ublemeter (mm) 165 Nominal Product Diameter (mm) 27 Diameter in mm) Weight (kg) 0.7 Packaging Single packaging type Carton Product EAN number 8711971339250 Packaging single length / height (cm) 17.0 Packaging single depth (cm) 18711971339257 Units per outer package 12 Packaging outer length / height (cm) 78.0		N
Total power consumption (W)	Beam Angle (°)	64
Total power consumption (W)	Electrical data	
Mains voltage (V) 220-240V Electrical protection Class II Control gear type Electronic ballast Transformer required Yes Dimming method N/A Drive current (mA) 350 Glow Wire Test (°C) 650 Energy Efficiency Class (A->G) of contained light source E Physical data Housing colour IP rating IP 44/20 IK rating IK vating IK va		2
Electrical protection Class II Control gear type Electronic ballast Transformer required Yes Dimming method N/A Drive current (mA) 350 Glow Wire Test (°C) 650 Energy Efficiency Class (A->G) of contained light source E Physical data Housing colour White IP rating IP44/20 IK rating IK02 Diffuser finish Opal Diffuser material PC Polycarbonate Reflector finish Other Nominal Product Length (mm) 165 Nominal Product Width (mm) 165 Nominal Product Diameter (mm) 165 Cutout Dimensions (W x L in mm or Diameter in mm) 165 Weight (kg) 0.7 Packaging Single packaging type Carton Product EAN number 8711971339250 Packaging single length / height (cm) 17.0 Packaging single depth (cm) 14.0 DUN14 (outer) 18711971339257 Units per outer package		
Control gear type		
Transformer required Yes Dimming method N/A Drive current (mA) 350 Glow Wire Test (°C) 650 Energy Efficiency Class (A->G) of contained light source E Physical data Housing colour White IP rating IP44/20 IK rating IK02 Diffuser finish Opal Diffuser material PC Polycarbonate Reflector finish Other Nominal Product Length (mm) 165 Nominal Product Width (mm) 165 Nominal Product Diameter (mm) 165 Cutout Dimensions (W x L in mm or Diameter in mm) 145 x 145 Diameter in mm) 0,7 Packaging Carton Product EAN number 8711971339250 Packaging single length / height (cm) 25.0 Packaging single width (cm) 17.0 Packaging single depth (cm) 14.0 DUN14 (outer) 18711971339257 Units per outer package 12 Packaging outer length / height (cm) 78.0	•	
Dimming method Drive current (mA) Glow Wire Test (°C) Energy Efficiency Class (A->G) of contained light source Physical data Housing colour IP rating IR rating IK rating IK rating IK rating Diffuser finish Opal Diffuser material Reflector finish Nominal Product Length (mm) Nominal Product Length (mm) Soundal Product Diameter (mm) Cutout Dimensions (W x L in mm or Diameter in mm) Weight (kg) Discolor Eackaging Single packaging type Packaging single length / height (cm) Packaging single depth (cm) Packaging outer length (r) Packaging outer length / height (cm) Packaging outer lengt		
Drive current (mA) 350 Glow Wire Test (°C) 650 Energy Efficiency Class (A->G) of contained light source Physical data Housing colour White IP rating IP44/20 IK rating IK02 Diffuser finish Opal Diffuser material PC Polycarbonate Reflector finish Other Nominal Product Length (mm) 165 Nominal Product Width (mm) 165 Nominal Product Diameter (mm) 165 Cutout Dimensions (W x L in mm or Diameter in mm) Weight (kg) 0.7 Packaging Single packaging type Carton Product EAN number 8711971339250 Packaging single length / height (cm) 12.0 Packaging single width (cm) 17.0 Packaging single depth (cm) 14.0 DUN14 (outer) 12.0 Packaging outer length / height (cm) 78.0		
Glow Wire Test (°C) 650 Energy Efficiency Class (A->G) of contained light source Physical data Housing colour White IP 44/20 IK rating IP 44/20 IK rating IK02 Diffuser finish Opal Other Mominal Product Length (mm) 165 Nominal Product Length (mm) 165 Nominal Product Leight (mm) 55 Nominal Product Diameter (mm) 165 Cutout Dimensions (W x L in mm or Diameter in mm) Weight (kg) 0.7 Packaging Single packaging type Carton Product EAN number 8711971339250 Packaging single length / height (cm) 14.0 DUN14 (outer) 12 Packaging outer length / height (cm) 78.0		
Energy Efficiency Class (A->G) of contained light source Physical data Housing colour IP rating IP 44/20 IK rating IK02 Diffuser finish Opal Diffuser material PC Polycarbonate Reflector finish Nominal Product Length (mm) Nominal Product Width (mm) Nominal Product Diameter (mm) Cutout Dimensions (W x L in mm or Diameter in mm) Weight (kg) Single packaging type Packaging single length / height (cm) Packaging single depth (cm) Packaging unter length / height (cm) Packaging outer length / height (cm) Rating Alexaging single width (cm) Packaging outer length / height (cm) Rating Alexaging single width (cm) Rating Alexaging single width (cm) Rating Alexaging single depth (cm) Rating Alexaging single width (cm) Rating Alexaging single depth (cm) Rating Alexaging single width (cm) Rating A	` ,	
Physical data Housing colour IP rating IP rating IK rating Diffuser finish Opal Diffuser material Reflector finish Nominal Product Length (mm) Nominal Product Height (mm) Nominal Product Diameter (mm) Cutout Dimensions (W x L in mm or Diameter in mm) Weight (kg) Single packaging type Packaging single length / height (cm) Packaging outer length (m) Packaging outer length / height (cm)	` ,	
Physical data Housing colour IP rating IP44/20 IK rating IK (C2 Diffuser finish Opal Diffuser material PC Polycarbonate Reflector finish Other Nominal Product Length (mm) 165 Nominal Product Width (mm) 165 Nominal Product Diameter (mm) Cutout Dimensions (W x L in mm or Diameter in mm) Weight (kg) Single packaging type Packaging Single packaging type Packaging single length / height (cm) Packaging single depth (cm) Packaging Verification Packaging single depth (mm) Packaging outer length (m) Packaging outer length / height (cm)		E
Housing colour IP rating IP 44/20 IK rating IK 2 Diffuser finish Opal Diffuser material Reflector finish Nominal Product Length (mm) Nominal Product Width (mm) 165 Nominal Product Diameter (mm) 165 Cutout Dimensions (W x L in mm or Diameter in mm) Weight (kg) Single packaging type Product EAN number Packaging single length / height (cm) Packaging single depth (cm) DUN14 (outer) Units per outer package 12 Packaging over length / height (cm) 78.0	Sometimes light source	
IP rating IP44/20 IK rating IK02 Diffuser finish Opal Diffuser material PC Polycarbonate Reflector finish Other Nominal Product Length (mm) 165 Nominal Product Width (mm) 165 Nominal Product Diameter (mm) 165 Cutout Dimensions (W x L in mm or Diameter in mm) Weight (kg) 0.7 Packaging Single packaging type Carton Product EAN number 8711971339250 Packaging single length / height (cm) 14.0 DUN14 (outer) 18711971339257 Units per outer package 12 Packaging outer length / height (cm) 78.0	Physical data	
IK rating IK02 Diffuser finish Opal Diffuser material PC Polycarbonate Reflector finish Other Nominal Product Length (mm) 165 Nominal Product Width (mm) 165 Nominal Product Height (mm) 55 Nominal Product Diameter (mm) 165 Cutout Dimensions (W x L in mm or Diameter in mm) Weight (kg) 0.7 Packaging Single packaging type Carton Product EAN number 8711971339250 Packaging single length / height (cm) 17.0 Packaging single depth (cm) 14.0 DUN14 (outer) 18711971339257 Units per outer package 12 Packaging outer length / height (cm) 78.0	Housing colour	White
Diffuser finish Diffuser material PC Polycarbonate Reflector finish Other Nominal Product Length (mm) 165 Nominal Product Width (mm) 165 Nominal Product Diameter (mm) 165 Cutout Dimensions (W x L in mm or Diameter in mm) Weight (kg) 0.7 Packaging Single packaging type Product EAN number Product EAN number Packaging single length / height (cm) Packaging single depth (cm) Packaging outer length / height (cm)	IP rating	IP44/20
Diffuser material PC Polycarbonate Reflector finish Other Nominal Product Length (mm) 165 Nominal Product Width (mm) 165 Nominal Product Height (mm) 55 Nominal Product Diameter (mm) 165 Cutout Dimensions (W x L in mm or Diameter in mm) Weight (kg) 0.7 Packaging Single packaging type Carton Product EAN number 8711971339250 Packaging single length / height (cm) 25.0 Packaging single width (cm) 17.0 Packaging single depth (cm) 14.0 DUN14 (outer) 18711971339257 Units per outer package 12 Packaging outer length / height (cm) 78.0	IK rating	IK02
Reflector finish Nominal Product Length (mm) 165 Nominal Product Width (mm) 165 Nominal Product Height (mm) 55 Nominal Product Diameter (mm) 165 Cutout Dimensions (W x L in mm or Diameter in mm) Weight (kg) 0.7 Packaging Single packaging type Product EAN number Packaging single length / height (cm) Packaging single depth (cm) 14.0 DUN14 (outer) Units per outer package 12 Packaging outer length / height (cm) 78.0	Diffuser finish	Opal
Nominal Product Length (mm) Nominal Product Width (mm) Nominal Product Height (mm) Nominal Product Length (mm) S5 Nominal Product Diameter (mm) Cutout Dimensions (W x L in mm or Diameter in mm) Weight (kg) O.7 Packaging Single packaging type Carton Product EAN number Product EAN number Packaging single length / height (cm) Packaging single width (cm) Packaging single depth (cm) 17.0 Packaging single depth (cm) DUN14 (outer) Units per outer package 12 Packaging outer length / height (cm) 78.0	Diffuser material	PC Polycarbonate
Nominal Product Width (mm) 165 Nominal Product Diameter (mm) 165 Cutout Dimensions (W x L in mm or Diameter in mm) Weight (kg) 0.7 Packaging Single packaging type Carton Product EAN number 8711971339250 Packaging single length / height (cm) 25.0 Packaging single width (cm) 17.0 Packaging single depth (cm) 14.0 DUN14 (outer) 18711971339257 Units per outer package 12 Packaging outer length / height (cm) 78.0	Reflector finish	Other
Nominal Product Height (mm) 55 Nominal Product Diameter (mm) 165 Cutout Dimensions (W x L in mm or Diameter in mm) Weight (kg) 0.7 Packaging Single packaging type Carton Product EAN number 8711971339250 Packaging single length / height (cm) 25.0 Packaging single width (cm) 17.0 Packaging single depth (cm) 14.0 DUN14 (outer) 18711971339257 Units per outer package 12 Packaging outer length / height (cm) 78.0	Nominal Product Length (mm)	165
Nominal Product Diameter (mm) 165 Cutout Dimensions (W x L in mm or Diameter in mm) Weight (kg) 0.7 Packaging Single packaging type Carton Product EAN number 8711971339250 Packaging single length / height (cm) 25.0 Packaging single width (cm) 17.0 Packaging single depth (cm) 14.0 DUN14 (outer) 18711971339257 Units per outer package 12 Packaging outer length / height (cm) 78.0	Nominal Product Width (mm)	165
Cutout Dimensions (W x L in mm or Diameter in mm) Weight (kg) O.7 Packaging Single packaging type Carton Product EAN number Packaging single length / height (cm) Packaging single width (cm) Packaging single depth (cm) DUN14 (outer) Units per outer package 12 Packaging outer length / height (cm) 78.0	Nominal Product Height (mm)	55
Diameter in mm) Weight (kg) 0.7 Packaging Single packaging type Carton Product EAN number Packaging single length / height (cm) Packaging single width (cm) Packaging single depth (cm) DUN14 (outer) Units per outer package 12 Packaging outer length / height (cm) 78.0	Nominal Product Diameter (mm)	
Weight (kg) Packaging Single packaging type Carton Product EAN number Packaging single length / height (cm) Packaging single width (cm) Packaging single depth (cm) DUN14 (outer) Units per outer package 12 Packaging outer length / height (cm) 78.0	Cutout Dimensions (W x L in mm or Diameter in mm)	145 x 145
Single packaging type Carton Product EAN number 8711971339250 Packaging single length / height (cm) 25.0 Packaging single width (cm) 17.0 Packaging single depth (cm) 14.0 DUN14 (outer) 18711971339257 Units per outer package 12 Packaging outer length / height (cm) 78.0	•	0.7
Single packaging type Carton Product EAN number 8711971339250 Packaging single length / height (cm) 25.0 Packaging single width (cm) 17.0 Packaging single depth (cm) 14.0 DUN14 (outer) 18711971339257 Units per outer package 12 Packaging outer length / height (cm) 78.0	B 4 :	
Product EAN number 8711971339250 Packaging single length / height (cm) 25.0 Packaging single width (cm) 17.0 Packaging single depth (cm) 14.0 DUN14 (outer) 18711971339257 Units per outer package 12 Packaging outer length / height (cm) 78.0		
Packaging single length / height (cm) 25.0 Packaging single width (cm) 17.0 Packaging single depth (cm) 14.0 DUN14 (outer) 18711971339257 Units per outer package 12 Packaging outer length / height (cm) 78.0		
Packaging single width (cm) 17.0 Packaging single depth (cm) 14.0 DUN14 (outer) 18711971339257 Units per outer package 12 Packaging outer length / height (cm) 78.0		
Packaging single depth (cm) 14.0 DUN14 (outer) 18711971339257 Units per outer package 12 Packaging outer length / height (cm) 78.0		
DUN14 (outer) 18711971339257 Units per outer package 12 Packaging outer length / height (cm) 78.0		
Units per outer package 12 Packaging outer length / height (cm) 78.0		
Packaging outer length / height (cm) 78.0		
Packaging outer width (cm) 36.0		
	Packaging outer width (cm)	36.0





Insaver HE Topper LED 150 PIR INSAVER 150 HE TOPPER LED NW PIR PLUS3 3033925

Packaging outer depth (cm)

31.0

PHOTOMETRY





TECHNICAL DRAWINGS

